



Material Safety Data Sheet

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M™ Bondo® Lightweight Body Filler 240, 260, 261, 261ES, 261M, 261C, 262, 262ES, 262M, 262C, 262ES, 262T, 262W, 265, 265C, 265ES, 265L, 265W, 267, 267C

MANUFACTURER: 3M

DIVISION: Automotive Aftermarket

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 01/06/12

Supersedes Date: 12/30/11

Document Group: 24-2445-5

ID Number(s):

60-4550-4828-4, 60-4550-4829-2, 60-4550-4988-6, 60-4550-5163-5, 60-4550-5494-4, 60-4550-5651-9, 60-4550-5652-7, 60-4550-5653-5, 60-4550-5654-3, 60-4550-5655-0, 60-4550-5782-2, 60-4550-5811-9, 60-4550-5812-7, 60-4550-5824-2, 60-4550-6588-2, 60-4550-6589-0, 60-4550-6590-8, 60-4550-6592-4, 60-4550-6737-5, 70-0080-0006-2, 70-0080-0007-0, 70-0080-0008-8, 70-0080-0044-3, 70-0080-0045-0, 70-0080-0047-6, 70-0080-0048-4, 70-0080-0052-6, 70-0080-0056-7, 70-0080-0058-3, 70-0080-0059-1

This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are:

24-7436-9, 24-2444-8

Revision Changes:

Kit: Component document group number(s) was modified.

Kit: ID Number(s) was modified.

Copyright was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2011, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M™ Bondo® Lightweight Body Filler 260, 261, 261C, 261E, 262, 262C, 262ES, 262L, 262T, 262W, 263, 264, 264S, 265, 265C, 265ES, 265T, 265W, 267, 267C

MANUFACTURER: 3M

DIVISION: Automotive Aftermarket

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 09/26/11

Supersedes Date: 05/03/11

Document Group: 24-2444-8

Product Use:

Intended Use: Automotive

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
1,3-ISOBENZOFURANDIONE, POLYMER WITH 2,5-FURANDIONE AND 2,2'-OXYBIS[ETHANOL]	26123-45-5	15 - 40
TALC	14807-96-6	10 - 30
STYRENE MONOMER	100-42-5	10 - 30
MAGNESIUM CARBONATE	546-93-0	7 - 15
OXIDE GLASS CHEMICALS	65997-17-3	5 - 10
QUATERNARY AMMONIUM COMPOUNDS, BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL, SALTS WITH MONTMORILLONITE	68911-87-5	1 - 5
LIMESTONE	1317-65-3	1 - 5
CHLORITE (MINERAL)	1318-59-8	0.1 - 2.0
QUARTZ SILICA	14808-60-7	0.1 - 1.0
TITANIUM DIOXIDE	13463-67-7	0.1 - 1.0

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Thick fibrous paste, styrene odor

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause target organ effects. Contains a chemical or chemicals which can cause cancer.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Inhalation:

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Prolonged or repeated exposure may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Prolonged or repeated exposure may cause:

Immunological Effects: Signs/symptoms may include alterations in the number of circulating immune cells, allergic skin and /or respiratory reaction, and changes in immune function.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient
QUARTZ SILICA

C.A.S. No.
14808-60-7

Class Description
Grp. I: Carcinogenic to humans

Regulation
International Agency for Research on Cancer

MATERIAL SAFETY DATA SHEET 3M™ Bondo® Lightweight Body Filler 260, 261, 261C, 261E, 262, 262C, 262ES, 262L, 262T, 262W, 263, 264, 264S, 265, 265C, 265ES, 265T, 265W, 267, 267C 09/26/11

SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	SEQ677	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	SEQ677	Known human carcinogen	National Toxicology Program Carcinogens
STYRENE MONOMER	100-42-5	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
TITANIUM DIOXIDE	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature	<i>No Data Available</i>
Flash Point	80 °F - 82 °F [<i>Test Method:</i> Closed Cup]
Flash Point	26.67 - 27.78 °C [<i>Test Method:</i> SETAFLASH]
Flammable Limits(LEL)	0.9 %
Flammable Limits(UEL)	6.8 %
OSHA Flammability Classification:	Class IC Flammable Liquid

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Water may be used to blanket the fire. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

6.2. Environmental precautions

Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Seal the container.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. No smoking while handling this material. Avoid breathing of vapors, mists or spray. Avoid static discharge. Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not breathe vapors. Do not breathe dust. Avoid contact with oxidizing agents.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Use in an enclosed process area is recommended. Provide appropriate local exhaust for cutting, grinding, sanding or machining. Do not use in a confined area or areas with little or no air movement.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact. Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields

Indirect Vented Goggles

.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Polyvinyl Alcohol (PVA)

Polymer laminate

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not breathe vapors. Do not breathe dust.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P95 particulate prefilters

. Select and use respiratory protection to prevent an inhalation exposure based on the results of an exposure assessment. Consult with your respirator manufacturer for selection of appropriate types of respirators.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Not applicable.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
LIMESTONE	OSHA	TWA, respirable fraction	5 mg/m3	
LIMESTONE	OSHA	TWA, as total dust	15 mg/m3	
MAGNESIUM CARBONATE	OSHA	TWA, respirable fraction	5 mg/m3	
MAGNESIUM CARBONATE	OSHA	TWA, as total dust	15 mg/m3	
OXIDE GLASS CHEMICALS	Manufacturer determined	TWA, as dust	10 mg/m3	
QUARTZ SILICA	ACGIH	TWA, respirable fraction	0.025 mg/m3	
QUARTZ SILICA	OSHA	TWA concentration, respirable	0.1 mg/m3	
QUARTZ SILICA	OSHA	TWA concentration, as total dust	0.3 mg/m3	
STYRENE MONOMER	ACGIH	TWA	20 ppm	
STYRENE MONOMER	ACGIH	STEL	40 ppm	
STYRENE MONOMER	OSHA	TWA	100 ppm	
STYRENE MONOMER	OSHA	CEIL	200 ppm	
TALC	ACGIH	TWA, respirable fraction	2 mg/m3	
TALC	CMRG	TWA, as respirable dust	0.5 mg/m3	
TALC	OSHA	TWA concentration, respirable	0.1 mg/m3	
TALC	OSHA	TWA concentration, as total dust	0.3 mg/m3	
TALC	OSHA	TWA	20 millions of particles/cu. ft.	
TITANIUM DIOXIDE	ACGIH	TWA	10 mg/m3	
TITANIUM DIOXIDE	CMRG	TWA, as respirable dust	5 mg/m3	
TITANIUM DIOXIDE	OSHA	TWA, as total dust	15 mg/m3	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Paste
Odor, Color, Grade:	Thick fibrous paste, styrene odor
General Physical Form:	Liquid
Autoignition temperature	<i>No Data Available</i>
Flash Point	80 °F - 82 °F [<i>Test Method:</i> Closed Cup]
Flash Point	26.67 - 27.78 °C [<i>Test Method:</i> SETAFLASH]
Flammable Limits(LEL)	0.9 %
Flammable Limits(UEL)	6.8 %
Boiling Point	293.00 °F [<i>Details:</i> CONDITIONS: (Styrene)]
Density	9.5126 lb/gal
Density	1.14 g/ml
Vapor Density	<i>No Data Available</i>
Vapor Pressure	5.2 mmHg [<i>Details:</i> CONDITIONS: at 20 C]
Specific Gravity	1.14 [<i>Ref Std:</i> WATER=1]
pH	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Solubility in Water	Nil
Evaporation rate	<i>No Data Available</i>
Hazardous Air Pollutants	17.8 % weight [<i>Test Method:</i> Calculated]
Volatile Organic Compounds	203 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Volatile Organic Compounds	17.8 % weight [<i>Test Method:</i> calculated per CARB title 2]
Kow - Oct/Water partition coef	<i>No Data Available</i>
Percent volatile	21.03 %
VOC Less H2O & Exempt Solvents	204 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
VOC Less H2O & Exempt Solvents	1.71 lb/gal [<i>Test Method:</i> calculated SCAQMD rule 443.1]

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

None known

10.2 Materials to avoid

Strong acids

Strong bases

Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons
Carbon monoxide
Carbon dioxide
Styrene Oxide
Toxic Vapor, Gas, Particulate

Condition

Not Specified
During Combustion
During Combustion
Not Specified
Not Specified

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in a permitted hazardous waste incinerator. Combustion products will include HCl. Facility must be capable of handling halogenated materials.

As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):

41-0003-6562-1, 41-0003-6642-1, 41-0003-6715-5, 41-3701-1570-5

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
STYRENE MONOMER	100-42-5	10 - 30

STATE REGULATIONS

Contact 3M for more information.

CALIFORNIA PROPOSITION 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	SEQ677	**Carcinogen

** WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 3 Reactivity: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Reason for Reissue: The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

Revision Changes:

Section 1: Product name was modified.

Section 1: Product use information was modified.

Section 4: First aid for eye contact - decontamination - was modified.

Section 4: First aid for eye contact - medical assistance - was modified.

Section 3: Potential effects from eye contact was modified.

Section 3: Potential effects from skin contact information was modified.

Section 10: Hazardous decomposition or by-products table was modified.

Section 3: Other health effects information was modified.

Page Heading: Product name was modified.

Section 9: Density information was modified.

Section 9: Vapor density value was modified.

Section 9: Vapor pressure value was modified.

Section 9: Boiling point information was modified.

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.
Section 5: Autoignition temperature information was modified.
Section 5: Flash point information was modified.
Section 9: Property description for optional properties was modified.
Section 9: Specific gravity information was modified.
Section 9: pH information was modified.
Section 9: Melting point information was modified.
Section 9: Solubility in water text was modified.
Section 9: Flash point information was modified.
Section 9: Flammable limits (LEL) information was modified.
Section 9: Flammable limits (UEL) information was modified.
Section 9: Autoignition temperature information was modified.
Section 14: ID Number(s) Template 1 was modified.
Section 2: Ingredient table was modified.
Section 15: EPCRA 313 information was modified.
Section 8: Exposure guidelines ingredient information was modified.
Section 3: Carcinogenicity table was modified.
Section 15: California proposition 65 ingredient information was modified.
Section 3: Immediate skin hazard(s) was deleted.
Section 3: Immediate eye hazard(s) was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2011, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M™ Red Cream Hardener
MANUFACTURER: 3M
DIVISION: Automotive Aftermarket
ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 04/13/11
Supersedes Date: 04/11/11

Document Group: 24-7436-9

Product Use:

Intended Use: Automotive

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
BENZOYL PEROXIDE	94-36-0	30 - 60
WATER	7732-18-5	10 - 30
BENZOIC ACID, C9-11-BRANCHED ALKYL ESTERS	131298-44-7	10 - 20
ZINC STEARATE	557-05-1	3 - 7
OXIRANE, POLYMER WITH METHYLOXIRANE, MONOBUTYL ETHER	9038-95-3	1 - 5
CALCIUM SULFATE	7778-18-9	1 - 5
IRON OXIDE (FE2O3)	1309-37-1	1 - 5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Viscous

Odor, Color, Grade: Red paste with slight ester odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: Closed containers exposed to heat from fire may build pressure and explode. Dust clouds of this material in combination with an ignition source may be explosive. May cause severe eye irritation. May cause allergic skin reaction.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Prolonged or repeated exposure may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

No Data Available

Flash Point

111 °C [*Test Method: Estimated*]

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Closed containers exposed to heat from fire may build pressure and explode. Dust clouds of this material in combination with an ignition source may be explosive.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

6.2. Environmental precautions

Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid static discharge. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid breathing of dust created by cutting, sanding, grinding or machining. Avoid eye contact with dust or airborne particles.

7.2 STORAGE

Store away from heat. Store out of direct sunlight. Keep container tightly closed. Do not heat under confinement to avoid risk of explosion

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Provide appropriate local exhaust for cutting, grinding, sanding or machining. Do not use in a confined area or areas with little or no air movement. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control dust, fume, or airborne particles. If ventilation is not adequate, use respiratory protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields

Indirect Vented Goggles

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Polymer laminate

Use an additional glove (e.g. supported PVC or Nitrile) over the PE/EVAL glove, and change the over-glove frequently.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. Avoid breathing of dust created by cutting, sanding, grinding or machining.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P95 particulate prefilters

Select and use respiratory protection to prevent an inhalation exposure based on the results of an exposure assessment. Consult with your respirator manufacturer for selection of appropriate types of respirators.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
ZINC STEARATE	OSHA	TWA, respirable fraction	5 mg/m3	
ZINC STEARATE	OSHA	TWA, as total dust	15 mg/m3	
BENZOYL PEROXIDE	ACGIH	TWA	5 mg/m3	
BENZOYL PEROXIDE	OSHA	TWA	5 mg/m3	
CALCIUM SULFATE	ACGIH	TWA, inhalable fraction	10 mg/m3	
CALCIUM SULFATE	OSHA	TWA, respirable fraction	5 mg/m3	
CALCIUM SULFATE	OSHA	TWA, as total dust	15 mg/m3	
IRON OXIDE (FE2O3)	ACGIH	TWA, respirable fraction	5 mg/m3	
IRON OXIDE (FE2O3)	OSHA	TWA, as fume	10 mg/m3	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Viscous
Odor, Color, Grade:	Red paste with slight ester odor
General Physical Form:	Solid
Autoignition temperature	<i>No Data Available</i>
Flash Point	111 °C [<i>Test Method:</i> Estimated]
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Boiling Point	<i>No Data Available</i>
Density	1.2 g/cm ³
Vapor Density	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Specific Gravity	1.2 [@ 25 °C] [<i>Ref Std:</i> WATER=1]
pH	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Solubility in Water	Negligible
Evaporation rate	<i>No Data Available</i>
Hazardous Air Pollutants	0 % weight [<i>Test Method:</i> Calculated]
Volatile Organic Compounds	0 lb/gal [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Volatile Organic Compounds	0 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Volatile Organic Compounds	0 % weight [<i>Test Method:</i> calculated per CARB title 2]
Kow - Oct/Water partition coef	<i>No Data Available</i>
Percent volatile	20 % [<i>Details:</i> Water is the volatile component]
VOC Less H₂O & Exempt Solvents	0 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Viscosity	<i>No Data Available</i>

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable. Stable unless exposed to heat, flames and drying conditions.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

10.2 Materials to avoid

Accelerators

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in a permitted hazardous waste incinerator in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):

LB-K100-0514-1, LB-K100-0530-2, LB-K100-0530-3, LB-K100-0530-4, LB-K100-0530-5, LB-K100-0926-4, 41-0003-6561-3, 41-0003-6569-6, 41-0003-6570-4, 41-0003-6571-2, 41-0003-6572-0, 41-0003-6639-7, 41-0003-6641-3, 41-3701-1487-2, 41-3701-1494-8

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - Yes Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
ZINC STEARATE (ZINC COMPOUNDS)	557-05-1	3 - 7
BENZOYL PEROXIDE	94-36-0	30 - 60

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 1 Reactivity: 1 Special Hazards: Oxidizer

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 1 Reactivity: 1 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

- Section 4: First aid for eye contact - decontamination - was modified.
- Section 4: First aid for eye contact - medical assistance - was modified.
- Section 3: Potential effects from eye contact was modified.
- Section 3: Potential effects from skin contact information was modified.
- Section 3: Immediate eye hazard(s) was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com