



Material Safety Data Sheet

Copyright, 2004, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: HFE-7100 3M (TM) Novec (TM) Engineered Fluid
MANUFACTURER: 3M
DIVISION: Electronics Markets Materials Division

ADDRESS: 3M Center
 St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 04/09/2004
Supersedes Date: 09/16/2003

Document Group: 07-6378-9

Product Use:

Intended Use: FOR INDUSTRIAL USE ONLY. NOT INTENDED FOR USE AS A MEDICAL DEVICE OR DRUG.
Specific Use: Cleaning and Coating Solvent; Heat Transfer Fluid

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
METHYL NONAFLUOROISOBUTYL ETHER	163702-08-7	20 - 80
METHYL NONAFLUOROBUTYL ETHER	163702-07-6	20 - 80

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: liquid

Odor, Color, Grade: Clear, colorless, liquid. Slight ethereal odor.

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: NONE KNOWN

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Inhalation:

If thermal decomposition occurs:

Respiratory Effects: Signs/symptoms may include cough, sneezing, shortness of breath, chest tightness, nasal discharge, and wheezing.

Ingestion:

No health effects are expected.

3.3 POTENTIAL ENVIRONMENTAL EFFECTS

A 3M Product Environmental Data Sheet (PED) is available.

This substance has chemical moieties that are resistant to biodegradation and is likely to only undergo partial biodegradation in the environment. The high potential of this substance to move from water to the atmosphere means its potential to bioconcentrate is likely to disappear rapidly from aerobic environments. Take precautions to prevent direct release of this product to the environment.

AQUATIC TOXICITY: Testing results indicate that this product has insignificant toxicity to aquatic organisms at its saturation point (Lowest LC50, EC50, or IC50 > substance water solubility). This substance is highly volatile and has a high Henry's Law constant and is thus expected to move rapidly through vaporization from solution in an aquatic compartment or from a soil surface in a terrestrial compartment to the atmosphere.

ATMOSPHERIC FATE: Zero Ozone Depletion Potential (ODP). Atmospheric Lifetime: approximately 4.1 yrs. Global Warming Potential (GWP): 280 (100 year ITH, IPCC1995 method). Global Warming Potential (GWP): 320 (100 yr ITH, IPCC2001 method). Atmospheric degradation products are expected to include: for methyl nonafluoroisobutyl ether: predominantly isoperfluorobutyric acid, CO₂, HF, and perhaps also CF₃COOH; for methyl nonafluorobutyl ether: n-perfluorobutyric acid, CO₂, and HF.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: If signs/symptoms develop, get medical attention. No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

405 °C [*Details:* (ASTM E659-84)]

Flash Point

No Flash Point acc to ASTM D56(CC) and ASTM D92-85 (OC) methods

Flammable Limits - LEL
Flammable Limits - UEL

[Details: NONE acc to ASTM E681-94, @100C]
[Details: NONE acc to ASTM E681-94, @100C]

5.2 EXTINGUISHING MEDIA

Material will not burn.

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may be used to blanket the fire. Exposure to extreme heat can give rise to thermal decomposition. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: No unusual fire or explosion hazards are anticipated. No unusual effects are anticipated during fire extinguishing operations. Avoid breathing the products and substances that may result from the thermal decomposition of the product or the other substances in the fire zone. Keep containers cool with water spray when exposed to fire to avoid rupture.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Ventilate the area with fresh air. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate organic solvent. Read and follow safety precautions on the solvent label and MSDS. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid skin contact with hot material. For industrial or professional use only. Contents may be under pressure, open carefully. No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of the hazardous decomposition products mentioned in the Reactivity Data section of this MSDS. Store work clothes separately from other clothing, food and tobacco products. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment. Avoid continuous exposure of the material to extreme conditions of heat, i.e., above 150 C (welding, open flame, misuse or equipment failure). Avoid exceeding a watt density of 50 watts/inch² from a heater surface. Continuous exposure to 150 C results in very slight decomposition of this product and therefore, is a very conservative use temperature threshold. Applications involving exposure of the fluid to temperatures exceeding 150 C or watt densities exceeding 50 watts/inch² have been safely implemented. Applications which may exceed these use parameters should be reviewed with 3M Technical Service.

7.2 STORAGE

Keep container tightly closed. Keep container in well-ventilated area. Store away from heat. Store away from strong bases.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide local exhaust ventilation at transfer points. Provide appropriate local exhaust when product is heated. For those situations where the fluid might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields.

8.2.2 Skin Protection

Avoid skin contact with hot material. Wear appropriate gloves, such as Nomex, when handling this material to prevent thermal burns.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance. If thermal degradation products are expected, use fullface supplied air respirator.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
METHYL NONAFLUOROBUTYL ETHER	AIHA	TWA	750 ppm	
METHYL NONAFLUROISOBTYL ETHER	AIHA	TWA	750 ppm	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:

liquid

Odor, Color, Grade:

Clear, colorless, liquid. Slight ethereal odor.

General Physical Form:

Liquid

Autoignition temperature

405 °C [Details: (ASTM E659-84)]

Flash Point

No Flash Point acc to ASTM D56(CC) and ASTM D92-85 (OC) methods

Flammable Limits - LEL

[Details: NONE acc to ASTM E681-94, @100C]

Flammable Limits - UEL	[Details: NONE acc to ASTM E681-94, @100C]
Boiling point	61 °C [@ 760 mmHg]
Density	1.5 g/ml
Vapor Density	8.6 [Ref Std: AIR=1]
Vapor Pressure	202 mmHg [@ 25 °C]
Specific Gravity	1.5 [Ref Std: WATER=1]
pH	Not Applicable
Melting point	-135 °C
Solubility In Water	< 12 ppm
Evaporation rate	49 [Ref Std: BUOAC=1]
Volatile Organic Compounds	[Details: Exempt]
Percent volatile	100 %
VOC Less H2O & Exempt Solvents	[Details: Exempt]
Viscosity	0.6 centipoise [@ 23 °C]

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Strong bases

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrogen Fluoride	At Elevated Temperatures - extreme conditions of heat
Perfluoroisobutylene (PFIB)	At Elevated Temperatures - extreme conditions of heat

Hazardous Decomposition: Perfluorinated Acid Fluorides

Hydrogen Fluoride has an ACGIH Threshold Limit Value of 3 parts per million (as fluoride) as a Ceiling Limit and an OSHA PEL of 3 ppm of fluoride as an eight hour Time_Weighted Average and 6 ppm of fluoride as a Short Term Exposure Limit. The odor threshold for HF is 0.04 ppm, providing good warning properties for exposure.

Decomposition of this product at temperatures above 300 degrees C can form perfluoroisobutylene (PFIB), but PFIB will only accumulate with continuous exposure to excessive heat in a sealed vessel. The formation rate for PFIB is about 1000 times less than the rate for primary thermal decomposition products such as HF. During normal use conditions, no health hazard is associated with the use of this material due to PFIB exposure.

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION**ECOTOXICOLOGICAL INFORMATION**

<u>Test Organism</u>	<u>Test Type</u>	<u>Result</u>
Fathead Minnow, Pimephales promelas	96 hours Lethal Concentration 50%	>7.9 mg/l
Green algae, Selenastrum capricornutum	96 hours Inhibitory Concentration 50%	>8.9 mg/l
Water flea, Daphnia magna	48 hours Effect Concentration 50%	>10 mg/l

CHEMICAL FATE INFORMATION

<u>Test Type</u>	<u>Result</u>	<u>Protocol</u>
	See Section 3.3.	

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Reclaim if feasible. As a disposal alternative, incinerate in an industrial or commercial facility in the presence of a combustible material. Combustion products will include HF. Facility must be capable of handling halogenated materials.

To reclaim or return, check product label for contact.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION**ID Number(s):**

98-0211-8940-6, 98-0211-8941-4, 98-0211-8942-2, 98-0211-8943-0, 98-0211-8944-8, 98-0211-8945-5, 98-0211-8946-3, 98-0212-1011-1, 98-0212-1035-0, 98-0212-1102-8, 98-0212-1128-3, 98-0212-1148-1, 98-0212-3138-0, 98-0212-3139-8, 98-0212-3140-6, 98-0212-3159-6

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION**US FEDERAL REGULATIONS**

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

Additional Information: The components of this product are in compliance with the chemical registration requirements of ELINCS, METI, AICS, KECI, PICCS, CICS, CEPA.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

ADDITIONAL INFORMATION

The U.S. Environmental Protection Agency (EPA) has listed 3M(TM) HFE-7100 as an acceptable substitute for ozone depleting substances in specific solvent cleaning and aerosol industry applications under its Significant New Alternatives Program (SNAP). Section 612 of the Clean Air Act requires the EPA to administer this program to evaluate and approve alternatives for ozone depleting substances.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Reactivity:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities. The hazard ratings assigned to this product are based on the properties of combustion or decomposition products that can occur in an uncontrolled fire situation.

HMIS Hazard Classification

Health: 0 **Flammability:** 1 **Reactivity:** 0 **Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS ®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 16: NFPA hazard classification heading was modified.
Section 16: HMIS hazard classification heading was modified.
Section 3: Potential environmental effects heading was modified.
Copyright was modified.
Section 8: Exposure guidelines data source legend was modified.
Section 5: Fire fighting procedures information was modified.

Section 15: 311/312 hazard categories heading was modified.
Section 15: International regulations information was modified.
Section 15: State regulations information was modified.
Section 15: US federal regulations information was modified.
Section 15: WHMIS regulations comment was modified.
Section 10: Hazardous polymerization heading was modified.
Section 15: WHMIS regulations comment heading was modified.
Section 16: HMIS explanation was modified.
Section 16: NFPA explanation was modified.
Section 15: Inventories information was modified.
Section 12: Ecotoxicological information heading was modified.
Section 12: Chemical fate information heading was modified.
Section 16: NFPA hazard classification for special hazards was modified.
Section 15: Inventories comment was modified.
Section 10: Hazardous decomposition heading was modified.
Section 2: Ingredient phrase was added.
Section 1: Secondary Division name was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com