# Class C Solutions Group

A business of MSC Industrial Supply Co.

# Safety Data Sheet

# Supply Co. - 64707896 BD1096 PTFE DRY LUBE

Document Nbr: 082650

Class C Parts IDs BD1096, BD1096-1

SAFETY DATA SHEET

ISSUING DATE: 02-JUN-2015

REVISION DATE: 13-JUN-2015

VERSI ON: 1.02

-----1. I DENTIFICATION OF THE SUBSTANCE/PREPARATION -----AND OF THE COMPANY/UNDERTAKING

PRODUCT IDENTIFIER:

PRODUCT NAME: 64707896 BD1096 PTFE DRY LUBE

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE:

PRODUCT CODE: F01539

PRODUCT TYPE: EXTREMELY FLAMMABLE AEROSOL

SYNONYMS: NONE

SUPPLIER'S DETAILS:

RECOMMENDED USE: DRY LUBRI CANT.

USES ADVISED AGAINST: NO INFORMATION AVAILABLE

MANUFACTURER:

AMERICAN JETWAY CORPORATION 34136 MYRTLE STREET WAYNE, MI 48184-0126

DI STRI BUTOR:

CLASS C SOLUTIONS GROUP
A BUSINESS OF MSC INDUSTRIAL SUPPLY CO.
75 MAXESS ROAD
MELVILLE, NY 11747-3151

1-866-438-6767

**EMERGENCY TELEPHONE NUMBER:** 

CHEMICAL EMERGENCY PHONE NUMBER: CHEMTREC: 1-800-262-8200 ID 1195

COMPANY EMERGENCY PHONE NUMBER: 734-721-5930

----2. HAZARDS IDENTIFICATION -----

CLASSI FI CATI ON:

SKIN CORROSION/IRRITATION: CATEGORY 2

SERIOUS EYE DAMAGE/EYE IRRITATION: CATEGORY 2A

REPRODUCTIVE TOXICITY: CATEGORY 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): CATEGORY 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): CATEGORY 2

ASPIRATION TOXICITY: CATEGORY 1 FLAMMABLE AEROSOLS: CATEGORY 1

GASES UNDER PRESSURE: COMPRESSED GAS

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS:

**EMERGENCY OVERVIEW:** 

DANGER:

HAZARD STATEMENTS:

CAUSES SKIN IRRITATION

CAUSES SERIOUS EYE IRRITATION

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD

MAY CAUSE DROWSINESS OR DIZZINESS

MAY CAUSE DAMAGE TO ORGANS (CENTRAL NERVOUS SYSTEM, EYES, PERIPHERAL NERVOUS SYSTEM, RESPIRATORY SYSTEM, AND SKIN) THROUGH PROLONGED OR REPEATED EXPOSURE.

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS

EXTREMELY FLAMMABLE AEROSOL

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

EXCLAMATION MARK
HEALTH HAZARD
FLAME
GAS CYLINDER

APPEARANCE: CLOUDY

PHYSICAL STATE: AEROSOL

ODOR: SOLVENT

PRECAUTIONARY STATEMENTS - PREVENTION:

OBTAIN SPECIAL INSTRUCTIONS BEFORE USE

DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD

WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION

WASH FACE, HANDS AND ANY EXPOSED SKIN THOROUGHLY AFTER HANDLING

DO NOT BREATHE DUST/FUME/GAS/MIST/VAPORS/SPRAY

USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA

KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING

DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE

PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE

PRECAUTIONARY STATEMENTS - RESPONSE:

IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION

SPECIFIC TREATMENT (SEE FIRST AID ON THIS LABEL)

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION

IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.

TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ATTENTION

IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL

IF SWALLOWED: IMMEDIATELY CALL A POISON CENTER OR DOCTOR/PHYSICIAN

DO NOT INDUCE VOMITING

PRECAUTIONARY STATEMENTS - STORAGE:

STORE LOCKED UP

STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F

PRECAUTIONARY STATEMENTS - DISPOSAL:

DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC): NONE

OTHER INFORMATION:

TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

6.02E-06% OF THE MIXTURE CONSISTS OF INGREDIENT(S) OF UNKNOWN TOXICITY

----3. COMPOSITION/INFORMATION ON INGREDIENTS -----

CAS # 110-54-3, HEXANE, MAY BE SUBSTITUTED FOR CAS # 64742-49-0, COMMERCIAL HEXANES.

| CHEMI CAL NAME              | CAS-NO     | WEIGHT %* |
|-----------------------------|------------|-----------|
| HEXANE                      | 110-54-3   | 50-60     |
| ACETONE                     | 67-64-1    | 20-30     |
| PROPANE/I SOBUTANE/N-BUTANE | 68476-86-8 | 10-20     |
| POLYTETRAFLUOROETHYLENE     | 9002-84-0  | 1-10      |

\*THE EXACT PERCENTAGE (CONCENTRATION) OF COMPOSITION HAS BEEN WITHHELD AS A TRADE SECRET.

----4. FIRST AID MEASURES -----

FIRST AID MEASURES FOR DIFFERENT EXPOSURE ROUTES:

### EYE CONTACT:

RINSE IMMEDIATELY WITH PLENTY OF WATER, ALSO UNDER THE EYELIDS, FOR AT LEAST 15 MINUTES. KEEP EYE WIDE OPEN WHILE RINSING. IF SYMPTOMS PERSIST, CALL A PHYSICIAN.

#### SKIN CONTACT:

WASH OFF IMMEDIATELY WITH SOAP AND PLENTY OF WATER WHILE REMOVING ALL CONTAMINATED CLOTHES AND SHOES. IF SYMPTOMS PERSIST, CALL A PHYSICIAN.

#### I NHALATI ON:

MOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. ARTIFICIAL RESPIRATION AND/OR OXYGEN MAY BE NECESSARY. IF BREATHING HAS STOPPED, CONTACT EMERGENCY MEDICAL SERVICES IMMEDIATELY.

#### I NGESTI ON:

RINSE MOUTH. DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

#### MAIN SYMPTOMS:

CAUSES EYE AND SKIN IRRITATION. IRRITATING TO RESPIRATORY SYSTEM. MAY CAUSE DROWSINESS OR DIZZINESS. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY:

NOTES TO PHYSICIAN: TREAT SYMPTOMATICALLY.

----5. FIRE-FIGHTING MEASURES -----

#### SUITABLE EXTINGUISHING MEDIA:

WATER FOG. DRY CHEMICAL. CARBON DIOXIDE (CO2). COOL CONTAINERS/TANKS WITH WATER SPRAY.

#### UNSUITABLE EXTINGUISHING MEDIA:

KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING. COOL CONTAINERS / TANKS WITH WATER SPRAY.

#### SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

EXTREMELY FLAMMABLE. KEEP PRODUCT AND EMPTY CONTAINER AWAY FROM HEAT AND SOURCES OF IGNITION. IN THE EVENT OF FIRE AND/OR EXPLOSION DO NOT BREATHE FUMES. IN THE EVENT OF FIRE, COOL TANKS WITH WATER SPRAY. RISK OF IGNITION.

#### **EXPLOSION DATA:**

SENSITIVITY TO MECHANICAL IMPACT: NONE. SENSITIVITY TO STATIC DISCHARGE: YES.

# PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS:

AS IN ANY FIRE, WEAR SELF-CONTAINED BREATHING APPARATUS PRESSURE-DEMAND, MSHA/NIOSH (APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR.

----6. ACCIDENTAL RELEASE MEASURES -----

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

#### PERSONAL PRECAUTIONS:

AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID BREATHING VAPORS OR MISTS. USE WITH ADEQUATE VENTILATION. KEEP CONTAINER AWAY FROM HEAT, FLAMES, AND ALL OTHER SOURCES OF IGNITION.

**ENVIRONMENTAL PRECAUTIONS:** 

#### **ENVIRONMENTAL PRECAUTIONS:**

BEWARE OF VAPORS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPORS CAN ACCUMULATE IN LOW AREAS. PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEM. PREVENT PRODUCT FROM ENTERING DRAINS. LOCAL AUTHORITIES SHOULD BE ADVISED IF SIGNIFICANT SPILLAGES CANNOT BE CONTAINED. DO NOT FLUSH INTO SURFACE WATER OR SANITARY SEWER SYSTEM.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

METHODS FOR CONTAINMENT:

ABSORB SPILL WITH INERT MATERIAL (E.G. DRY SAND OR EARTH), THEN PLACE IN A CHEMICAL WASTE CONTAINER. STOP LEAK IF YOU CAN DO IT WITHOUT RISK.

METHODS FOR CLEANING UP:

PICK UP AND TRANSFER TO PROPERLY LABELED CONTAINERS. SOAK UP WITH INERT ABSORBENT MATERIAL. CLEAN CONTAMINATED SURFACE THOROUGHLY. AFTER CLEANING, FLUSH AWAY TRACES WITH WATER. TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.

----7. HANDLING AND STORAGE -----

PRECAUTIONS FOR SAFE HANDLING:

ADVICE ON SAFE HANDLING:

AVOID CONTACT WITH EYES. AVOID BREATHING VAPORS OR MISTS. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE CANS. DO NOT STICK PIN OR ANY OTHER SHARP OBJECT INTO OPENING ON TOP OF CAN.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

TECHNICAL MEASURES/STORAGE CONDITIONS:

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. KEEP AWAY FROM OPEN FLAMES, HOT SURFACES AND SOURCES OF IGNITION. KEEP IN PROPERLY LABELED CONTAINERS. KEEP OUT OF THE REACH OF CHILDREN. STORE LOCKED UP.

INCOMPATIBLE PRODUCTS: STRONG ACIDS, ALKALIS, OR OXIDIZING AGENTS.

AEROSOL LEVEL: 3

----8. EXPOSURE CONTROLS/PERSONAL PROTECTION -----

CONTROL PARAMETERS:

**EXPOSURE GUIDELINES:** 

OSHA PEL NIOSH IDLH CHEMICAL NAME ACGIH TLV HEXANE TWA: 50 PPM TWA: 500 PPM IDLH: 1100 PPM 110-54-3 TWA: 1800 MG/M3 TWA: 50 PPM SKIN -POTENTI AL TWA: 180 MG/M3 SI GNI FI CANT (VACATED) TWA: CONTRIBUTION TO 50 PPM OVERALL EXPOSURE BY THE CUTANEOUS (VACATED) TWA: ROUTE 180 MG/M3

ACETONE STEL: 750 PPM TWA: 1000 PPM I DLH: 2500 PPM 67-64-1 TWA: 500 PPM TWA: 2400 MG/M3 TWA: 250 PPM

TWA: 590 MG/M3

TWA: 1800 MG/M3

106-97-8:

(VACATED) TWA:

750 PPM

(VACATED) TWA: 1800 MG/M3

(VACATED) STEL: 2400 MG/M3

THE ACETONE STEL
DOES NOT APPLY TO
THE CELLULOSE
ACETATE FIBER
INDUSTRY. IT IS
IN EFFECT FOR ALL
OTHER SECTORS

(VACATED) STEL:

1000 PPM

1000 PPM

PROPANE/ 74-98-6: 74-98-6: 74-98-6:

68476-86-8 106-97-8:

STEL: 1000 PPM (VACATED) TWA:

75-28-5: TWA: 800 PPM

75-20-5. TWA. 000 FFW

STEL: 1000 PPM (VACATED) TWA: TWA: 1900 MG/M3 1800 MG/M3

75-28-5:

106-97-8: TWA: 800 PPM (VACATED) TWA: TWA: 1900 MG/M3

800 PPM

(VACATED) TWA: 1900 MG/M3

ACGIH: (AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS)

OSHA: (OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION)

NIOSH IDLH: IMMEDIATELY DANGEROUS TO LIFE OR HEALTH

OTHER EXPOSURE GUIDELINES:

VACATED LIMITS REVOKED BY THE COURT OF APPEALS DECISION IN AFL-CIO V. OSHA, 965 F. 2D 962 (11TH CIR., 1992).

EXPOSURE CONTROLS:

ENGINEERING MEASURES:

SHOWERS
EYEWASH STATIONS
VENTILATION SYSTEMS.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION: SAFETY GLASSES WITH SIDE-SHIELDS.

SKIN AND BODY PROTECTION: CHEMICAL RESISTANT APRON. PROTECTIVE GLOVES.

#### RESPIRATORY PROTECTION:

IF EXPOSURE LIMITS ARE EXCEEDED OR IRRITATION IS EXPERIENCED, NIOSH/MSHA APPROVED RESPIRATORY PROTECTION SHOULD BE WORN. POSITIVE-PRESSURE SUPPLIED AIR RESPIRATORS MAY BE REQUIRED FOR HIGH AIRBORNE CONTAMINANT CONCENTRATIONS. RESPIRATORY PROTECTION MUST BE PROVIDED IN ACCORDANCE WITH CURRENT LOCAL REGULATIONS.

#### HYGI ENE MEASURES:

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE.

----9. PHYSICAL AND CHEMICAL PROPERTIES -----

PHYSICAL AND CHEMICAL PROPERTIES:

PHYSICAL STATE: AEROSOL

APPEARANCE: CLOUDY

ODOR: SOLVENT

COLOR: WHITE

ODOR THRESHOLD: NO INFORMATION AVAILABLE

PROPERTY VALUES REMARKS - METHODS

PH NO INFORMATION AVAILABLE

MELTING/FREEZING POINT NO INFORMATION AVAILABLE

BOILING POINT/BOILING RANGE NO INFORMATION AVAILABLE

FLASH POINT -97 DEG. C / -142 DEG. F BASED ON PROPELLANT

EVAPORATION RATE NO INFORMATION AVAILABLE

FLAMMABILITY (SOLID, GAS) NO INFORMATION AVAILABLE

FLAMMABILITY LIMITS IN AIR:

UPPER FLAMMABILITY LIMIT NO INFORMATION AVAILABLE LOWER FLAMMABILITY LIMIT NO INFORMATION AVAILABLE

VAPOR PRESSURE NO INFORMATION AVAILABLE

VAPOR DENSITY NO INFORMATION AVAILABLE

SPECIFIC GRAVITY NO INFORMATION AVAILABLE

WATER SOLUBILITY PRACTICALLY INSOLUBLE

PARTITION COEFFICIENT

N-OCTANOL/WATER

NO INFORMATION AVAILABLE

AUTOIGNITION TEMPERATURE NO INFORMATION AVAILABLE NOT APPLICABLE

DECOMPOSITION TEMPERATURE NO INFORMATION AVAILABLE

VISCOSITY NO INFORMATION AVAILABLE

EXPLOSIVE PROPERTIES NO INFORMATION AVAILABLE

OTHER INFORMATION:

VOC CONTENT(%) 77. 43

MIR VALUE 1.08

-----10. STABILITY AND REACTIVITY -----

REACTIVITY: NO DATA AVAILABLE

CHEMICAL STABILITY: STABLE UNDER RECOMMENDED STORAGE CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS: NONE UNDER NORMAL PROCESSING.

CONDITIONS TO AVOID: EXTREMES OF TEMPERATURE AND DIRECT SUNLIGHT.

INCOMPATIBLE MATERIALS: STRONG ACIDS, ALKALIS, OR OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS:

NONE KNOWN BASED ON INFORMATION SUPPLIED.

-----11. TOXICOLOGICAL INFORMATION -----

INFORMATION ON LIKELY ROUTES OF EXPOSURE:

PRODUCT INFORMATION:

I NHALATI ON:

VAPORS MAY IRRITATE THROAT AND RESPIRATORY SYSTEM. MAY CAUSE DROWNSINESS AND DIZZINESS BASED ON COMPONENTS. MAY CAUSE IRRITATION OF RESPIRATORY TRACT. AVOID BREATHING VAPORS OR MISTS.

EYE CONTACT: IRRITATING TO EYES. AVOID CONTACT WITH EYES.

#### SKIN CONTACT:

IRRITATING TO SKIN. REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING. PROLONGED SKIN CONTACT MAY DEFAT THE SKIN AND PRODUCE DERMATITIS. AVOID CONTACT WITH SKIN.

#### I NGESTI ON:

MAY BE HARMFUL OR FATAL IF SWALLOWED. ASPIRATION INTO THE LUNGS DURING SWALLOWING MAY CAUSE SERIOUS LUNG DAMAGE WHICH MAY BE FATAL.

#### COMPONENT INFORMATION:

| CHEMI CAL NAME | LD50 ORAL   | LD50 DERMAL  | LC50 INHALATION |
|----------------|-------------|--------------|-----------------|
| HEXANE         |             | =3000 MG/KG  | =48000 PPM      |
| 110-54-3       |             | (RABBIT)     | (RAT) 4 H       |
| ACETONE        | =5800 MG/KG | 20,000 MG/KG | =50100 MG/M3    |
| 67-64-1        |             | (RABBIT)     | (RAT) 8 H       |

#### INFORMATION ON TOXICOLOGICAL EFFECTS:

#### SYMPTOMS:

SYMPTOMS OF OVEREXPOSURE MAY BE HEADACHE, DIZZINESS, TIREDNESS, NAUSEA, AND VOMITING. CAUSES SKIN AND EYE IRRITATION. MAY CAUSE RESPIRATORY SYSTEM IRRITATION. PROLONGED OR REPEATED EXPOSURE MAY CAUSE DERMATITIS. NOT ACUTELY TOXIC. ASPIRATION INTO THE LUNGS DURING SWALLOWING MAY CAUSE SERIOUS LUNG DAMAGE WHICH MAY BE FATAL.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

SKIN CORROSION/IRRITATION: IRRITATING TO SKIN.

EYE DAMAGE/IRRITATION: IRRITATING TO EYES.

IRRITATION: IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

SENSITIZATION: NONE KNOWN.

GERM CELL MUTAGENICITY: NONE KNOWN.

CARCINOGENICITY: THERE ARE NO KNOWN CARCINOGENIC CHEMICALS IN THIS PRODUCT.

CHEMICAL NAME ACGIH LARC NTP OSHA

POLYTETRAFLUOROETHYLENE GROUP 3

9002-84-0

## REPRODUCTIVE TOXICITY:

PRODUCT IS OR CONTAINS A CHEMICAL WHICH IS A KNOWN OR SUSPECTED REPRODUCTIVE HAZARD.

10 of 15

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE):
MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS AND DIZZINESS.

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE): MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

TARGET ORGAN EFFECTS:

CENTRAL NERVOUS SYSTEM, EYES, RESPIRATORY SYSTEM, SKIN, PERIPHERAL NERVOUS SYSTEM (PNS).

NEUROLOGICAL EFFECTS:

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENTS MAY BE HARMFUL OR FATAL.

ASPIRATION HAZARD: MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

NUMERICAL MEASURES OF TOXICITY - PRODUCT INFORMATION:

UNKNOWN ACUTE TOXICITY:

6.02E-06% OF THE MIXTURE CONSISTS OF INGREDIENT(S) OF UNKNOWN TOXICITY

THE FOLLOWING VALUES ARE CALCULATED BASED ON CHAPTER 3.1 OF THE GHS DOCUMENT:

ATEMIX (DERMAL): 5223 MG/KG

ATEMIX (INHALATION-VAPOR): 83569 MG/L

----12. ECOLOGICAL INFORMATION -----

ECOTOXICITY:

CHEMICAL NAME TOXICITY TO ALGAE TOXICITY TO FISH

HEXANE 2. 1 - 2. 98 MG/L LC50 110-54-3 PI MEPHALES PROMELAS 96H

FLOW-THROUGH

ACETONE 4. 74 - 6. 33 ML/L LC50 67-64-1 ONCORHYNCHUS MYKI SS 96H

6210 - 8120 MG/L LC50 PIMEPHALES PROMELAS 96H

STATI C

8300 MG/L LC50

LEPOMIS MACROCHIRUS 96H

PROPANE/I SOBUTANE/ N-BUTANE 68476-86-8

CHEMICAL NAME TOXICITY TO TOXICITY TO DAPHNIA AND

MI CROORGANI SMS

OTHER AQUATIC INVERTEBRATES

**HEXANE** 

ACETONE 10294 - 17704 MG/L EC50

DAPHNIA MAGNA 48H STATIC

12600 - 12700 MG/L EC50

DAPHNIA MAGNA 48H

PROPANE/I SOBUTANE/

N-BUTANE

PERSISTENCE AND DEGRADABILITY: NO INFORMATION AVAILABLE.

BIOACCUMULATION: NO INFORMATION AVAILABLE.

CHEMI CAL NAME LOG POW

ACETONE -0. 24

67-64-1

PROPANE/I SOBUTANE/N-BUTANE 2. 8

68476-86-8

OTHER ADVERSE EFFECTS: NO INFORMATION AVAILABLE

-----13. DISPOSAL CONSIDERATIONS -----

WASTE TREATMENT:

WASTE DI SPOSAL METHODS:

THIS MATERIAL, AS SUPPLIED, IS A HAZARDOUS WASTE ACCORDING TO FEDERAL REGULATIONS (40 CFR 261).

CONTAMINATED PACKAGING: DO NOT RE-USE EMPTY CONTAINERS.

----14. TRANSPORT INFORMATION -----

DOT GROUND:

CONSUMER COMMODITY ORM-D

OR

LIMITED QUANTITY

IATA: UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG: UN1950, AEROSOLS, 2.1, LTD. QTY.

----15. REGULATORY INFORMATION -----

#### INTERNATIONAL INVENTORIES:

| CHEMI CAL NAME                      | TSCA | DSL/NDSL | EI NECS/<br>ELI NCS | ENCS           | LECSC | KECL | PICCS | AICS |
|-------------------------------------|------|----------|---------------------|----------------|-------|------|-------|------|
| HEXANE                              | Х    | Χ        | Χ                   | Χ              | Х     | Х    | Х     | Χ    |
| ACETONE                             | Х    | Χ        | Χ                   | X              | X     | Χ    | Х     | Χ    |
| PROPANE/<br>I SOBUTANE/<br>N-BUTANE | X    | Х        | X                   | NOT<br>LI STED | X     | X    | X     | X    |
| POLYTETRAFLUORO-<br>ETHYLENE        | X    | Χ        | NOT<br>LI STED      | Χ              | X     | Х    | X     | Х    |

#### LEGEND:

TSCA: UNITED STATES TOXIC SUBSTANCES CONTROL ACT SECTION 8(B) INVENTORY

DSL/NDSL: CANADIAN DOMESTIC SUBSTANCES LIST/NON-DOMESTIC SUBSTANCES LIST

#### EI NECS/ELI NCS:

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES/EU LIST OF NOTIFIED CHEMICAL SUBSTANCES

ENCS: JAPAN EXISTING AND NEW CHEMICAL SUBSTANCES

CHINA: CHINA INVENTORY OF EXISTING CHEMICAL SUBSTANCES

KECL: KOREAN EXISTING AND EVALUATED CHEMICAL SUBSTANCES

PICCS: PHILIPPINES INVENTORY OF CHEMICALS AND CHEMICAL SUBSTANCES

ALCS: AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES

#### U.S. FEDERAL REGULATIONS:

#### SARA 313:

SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA). THIS PRODUCT CONTAINS A CHEMICAL OR CHEMICALS WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS OF THE ACT AND TITLE 40 OF THE CODE OF FEDERAL REGULATIONS, PART 372:

CHEMICAL NAME CAS-NO WEIGHT %\* SARA 313 - THRESHOLD VALUES %

HEXANE - 110-54-3 110-54-3 50-60 10

SARA 311/312 HAZARD CATEGORIES:

ACUTE HEALTH HAZARD: YES CHRONI C HEALTH HAZARD: YES

FIRE HAZARD: YES

SUDDEN RELEASE OF PRESSURE HAZARD: YES

RQ:

2270 KG FINAL RQ

REACTIVE HAZARD: NO

#### CLEAN WATER ACT:

THIS PRODUCT DOES NOT CONTAIN ANY SUBSTANCES REGULATED AS POLLUTANTS PURSUANT TO THE CLEAN WATER ACT (40 CFR 122.21 AND 40 CFR 122.42).

#### CERCLA:

THIS MATERIAL, AS SUPPLIED, CONTAINS ONE OR MORE SUBSTANCES REGULATED AS A HAZARDOUS SUBSTANCE UNDER THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) (40 CFR 302):

| CHEMI CAL NAME     | HAZARDOUS SUBSTANCES<br>RQS | EXTREMELY HAZARDOUS<br>SUBSTANCES RQS | RQ                      |
|--------------------|-----------------------------|---------------------------------------|-------------------------|
| HEXANE<br>110-54-3 | 5000 LB                     |                                       | RQ:<br>5000 LB FINAL RQ |
|                    |                             |                                       | RQ:<br>2270 KG FINAL RQ |
| ACETONE<br>67-64-1 | 5000 LB                     |                                       | RQ:<br>5000 LB FINAL RQ |

#### U. S. STATE REGULATIONS:

CALIFORNIA PROPOSITION 65: NO WARNING REQUIRED.

#### U.S. STATE RIGHT-TO-KNOW REGULATIONS:

| CHEMI CAL NAME                       | NEW JERSEY | MASSACHUSETTS | PENNSYLVANI A |
|--------------------------------------|------------|---------------|---------------|
| HEXANE<br>110-54-3                   | X          | X             | X             |
| ACETONE<br>67-64-1                   | X          | Х             | X             |
| POLYTETRAFLUOROETHYLENE<br>9002-84-0 |            |               | X             |

EPA PESTICIDE REGISTRATION NUMBER: NOT APPLICABLE

#### CANADA:

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

A - COMPRESSED GAS

- B FLAMMABLE AND COMBUSTIBLE MATERIAL
- D2 MATERIALS CAUSING OTHER TOXIC EFFECTS

## ----16. OTHER INFORMATION -----

NFPA:

HEALTH HAZARD 2
FLAMMABILITY 4
INSTABILITY 0
PHYSICAL AND CHEMICAL HAZARDS

HMI S:

HEALTH HAZARD 2\*
FLAMMABILITY 4
PHYSICAL HAZARD 1
PERSONAL PROTECTION B

CHRONIC HAZARD STAR LEGEND:

CHRONIC HEALTH HAZARD; REPEATED OR PROLONGED EXPOSURE MAY CAUSE CENTRAL

NERVOUS SYSTEM DAMAGE

PREPARED BY:
AMERICAN JETWAY
34136 MYRTLE STREET
WAYNE, MI 48184

TEL.: 734-721-5930

ISSUING DATE: 02-JUN-2015

REVISION DATE: 13-JUN-2015

REVISION NOTE: NO INFORMATION AVAILABLE

#### DI SCLAI MER:

THE INFORMATION PROVIDED ON THIS SDS IS CORRECT TO THE BEST OF OUR KNOWLEDGE, INFORMATION AND BELIEF AT THE DATE OF ITS PUBLICATION. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED AS A WARRANTY OR QUALITY SPECIFICATION. THE INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS, UNLESS SPECIFIED IN THE TEXT.

15 of 15