

AP-5™

HIGH-TEMP MULTI-PURPOSE GREASE

DESCRIPTION

Formulated from bentone clay, **AP-5™** is noted for its high temperature insensitivity, is nonmelting and does not thicken excessively at temperatures as low as 0°F (-18°C). It has mechanical stability, is water resistant, displays high stability on working, has excellent adhesion to metals, prevents wear and has superior storage life.

AP-5 contains molybdenum disulfide, oxidation inhibitors, corrosion inhibitors and metal deactivators. It offers positive protection for extreme services, which require heavy duty lubricant performance.

JET-LUBE's AP-5 is recommended for anti-friction bearings, ball and roller bearings, sleeve bearings, journals, shackles, slides, conveyor chains, U-joints, sealed assemblies, chassis and general lubrication.

- Protects against rust and corrosion
- Prevents wear
- Highly adhesive to metal
- Resistant to water
- Superior storage life
- Color-Black

APPLICATIONS

JET-LUBE's AP-5 is a black, smooth, nonmelting, water resistant grease. It contains molybdenum disulfide (MoS₂) to yield high film strength with low coefficient of friction. Resists fretting corrosion. Suitable for use in plain and anti-friction ball and roller bearings. Provides heavy-duty protection for such heavy-industry equipment as kiln bearings, crushers, crane ladles, press and hammer guides and lift-bridge pin bearings. **AP-5** is especially recommended for lubrication points prone to neglect such as motors, high temperature blowers, fans and oven conveyors.

OPERATING RANGE:
0°F (-18°C) to 550°F (288°C)

PRODUCT CHARACTERISTICS

Thickener	Organo Clay
Fluid Type	Lube Oil
Color	Black
Dropping Point (ASTM D-566)	None
Specific Gravity	0.92
Density (lb/gal)	7.70
Additive Type	Organic & MoS ₂
Flash Point (ASTM D-92)	>560°F (293°C)
Autoignition Point (CALCULATED)	>680°F (360°C)
NLGI Grade	2
Penetration @77°F (ASTM D-217)	265 - 295
Copper Strip Corrosion (ASTM D-4048)	1A
Shell 4-Ball (ASTM D-2596)	
Weld Point, kgf	250
Load Wear Index	40
Wear Scar Diameter (ASTM D-2266)	0.7
Oxidation Resistance (ASTM D-942)	
PSI Drop, 100 hours	<5.0
Base Oil Viscosity (ASTM D-445)	
cSt @ 40°C	414 - 506

PACKAGING

Code No.	Container Size	Container
25050	14 oz.	Cartridge
25005	1 lb.	Can
25006	5 lb.	Can
25016	35 lb.	Pail
25024	120 lb.	Drum
25029	400 lb.	Drum

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC.
4849 HOMESTEAD RD.,
SUITE 232
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-670-5700
FAX: 713-678-4604
sales@jetlube.com
www.jetlube.com

JET-LUBE, INC.

MATERIAL SAFETY DATA SHEET

Product Name: AP-5™
Chemical Family: Lubricating grease
Use: Equipment lubrication

Manufacturer/Supplier: JET-LUBE, INC.
Address: 4849 Homestead Rd., Ste. #232
 Houston, TX, 77028 USA **Phone:** 713-670-5700
Emergency Phone: 713-670-5700 **Fax:** 713-678-4604
Chemtrec 24 hours (USA): 800-424-9300
Outside the USA: 703-527-3887

Hazardous Components	CAS No.	Wt%	OSHA PEL	ACGIH TLV	Other Limits of Exposure
Petroleum oil	64742014/64742525	60-100	Oil mist TWA-5mg/M ³	N/A	STEL: 10mg/M ³
Nonhazardous Blend	68953582/1317335 108327/9003274	10-15	N/A	N/A	N/A

Main Hazards—Health Effects

Eyes: May cause irritation. **Inhalation:** Viscous nature may block breathing passages if inhaled. **Ingestion:** May cause diarrhea.
Skin: For hypersensitive persons, may irritate the skin after prolonged periods of contact.

Eyes: Flush with water until all residual material is gone. If irritation persists, seek medical help. **Inhalation:** Clear air passage. If respiratory difficulty continues, seek medical help. **Ingestion:** Wash out mouth immediately. Consult physician. **Skin:** Wash thoroughly with hand cleanser, followed by soap & water. Contaminated clothing should be dry cleaned before reuse.

Extinguishing Media: Foam, dry powder, Halon®, carbon dioxide, sand, earth & water mist. **Unsuitable Extinguishing Media:** Water jet.
Protective Equipment for Fire fighting: Self-contained breathing apparatus.

Personal Precautions: Wear nitrile gloves & protective overalls. **Environmental Precautions:** Do not allow it to enter drains. **Spillage:** Scrape up bulk, then wipe up remainder with cloth. To prevent walking hazard, pick up remaining residue with diatomaceous earth.

Handling: No special handling precautions necessary. **Storage:** Do not store at elevated temperatures.

Respiratory Protection: None needed. **Hand Protection:** Nitrile gloves for hypersensitive persons. **Eye Protection:** Glasses, if applied to parts in motion. **Body Protection:** Overalls.

Physical State: Semisolid paste **Color:** Black **Odor:** Petroleum **pH:** Neutral **Boiling Range/Point °F (°C):** >700 (371)
Melting Point °F (°C): N/A **Flash Point (COC) °F (°C):** >560 (293) **Autoignition Temperature °F (°C):** >680 (360)
Explosive Properties: LEL: 0.9% UEL: 7% **Evaporation Rate (Butyl Acetate):** <0.01 **Partition Coefficient (Log Pow):** N/A
Vapor Pressure (kPa): <0.01 **Percent Volatiles:** Nil **Density (g/cm³):** 7.70 **Flammability:** Not flammable at ambient temperature.
OAR Value: N/A **Oxidizing Properties:** None **Water Solubility:** Slight, not readily soluble **Vapor Density:** >5

Stability: Chemically stable under normal conditions. No photoreactive agents. **Conditions to Avoid:** Powerful sources of ignition and extreme temperatures. **Materials to Avoid:** Strong inorganic & organic acids, oxidizing agents. **Hazardous Decomposition Products:** Burning generates smoke, airborne soot, hydrocarbons and oxides of carbon, sulfur and nitrogen. Residue mainly comprised of soot & mineral oxides.

Acute Toxicity: Not known. **Irritancy—Skin:** Very mild. **Skin Sensitization:** Not known. **Subacute/Sub-chronic Toxicity:** Not known.
Genotoxicity: None known. **Chronic Toxicity:** None known. **California Prop 65:** N/A **Carcinogen:** NTP: No IARC: No **OSHA:** No
EC Classification (67/548/EEC): No **LC-50:** >2000mg/l—extrapolated from component data. **LD-50:** Not applicable

Possible Effects: In extreme cases, may generate oil fractions that could act as a marine pollutant. Occurrences of this nature are highly unlikely. **Behavior:** Relatively well behaved. Bioaccumulation potential nil. **Environmental Fate:** Highly unlikely to cause widespread contamination. Nontoxic to marine or land organisms.

Product Disposal: Do not incinerate. Contact waste disposal company or local authority for advice. **Container Disposal:** Pails without liner—see Product Disposal section above. **Pails with plastic liner—**pail may only be disposed of via standard waste disposal services, recycled or reused. **Liner—**see Product Disposal section above.

Not classified as hazardous for transport **D.O.T.:** Nonhazardous **UN No.:** Nonhazardous **Air Transport (ICAO & IATA):** Nonhazardous
Sea Transport (IMO & IMDG): Nonhazardous **Road & Rail Transport (ADR/RID):** Nonhazardous

Labeling Information: None needed. **EC Annex 1 Classification:** Not Applicable. **R Phrases:** R22—harmful if swallowed.
S Phrases: None applicable, as known. **Ozone Depleting Chemicals:** Not applicable. **TSCA:** All components are listed.
WHMIS (Canada): Not controlled. **Canadian DSL:** All components listed. **40 CFR Part 372 (SARA Section 313):** N/A
CERCLA: Nonhazardous **RCRA Hazard Class:** Nonhazardous **SARA 311/312:** None **TSCA 12B Components:** None

SDS first issued. SDS data revised. **New Jersey Right To Know:** See Section II

LEGEND


- I. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY
- II. COMPOSITION INFORMATION ON INGREDIENTS
- III. HAZARDS IDENTIFICATION
- IV. FIRST AID MEASURES
- V. FIRE FIGHTING MEASURES
- VI. ACCIDENTAL RELEASE MEASURES
- VII. HANDLING AND STORAGE
- VIII. EXPOSURE CONTROL/PERSONAL PROTECTION
- IX. PHYSICAL AND CHEMICAL PROPERTIES
- X. STABILITY AND REACTIVITY
- XI. TOXICOLOGICAL INFORMATION
- XII. ECOLOGICAL INFORMATION
- XIII. WASTE DISPOSAL
- XIV. TRANSPORT INFORMATION
- XV. REGULATORY INFORMATION
- XVI. OTHER INFORMATION

HMIS SYMBOL

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PPI	B

NFPA SYMBOL



Signature: 
Prepared by: Donald A. Oldiges
Date Issued: August 24, 2009

As of issue date, the information contained herein is accurate and reliable to the best of JET-LUBE'S knowledge. JET-LUBE® does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the user's responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.