## **Material Safety Data Sheet**





Revision Number: 005.1 Issue date: 03/01/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE® 515™ GASKET

**ELIMINATOR® FLANGE SEALANT** 

PART NO. 51531

**Product type:** Anaerobic Adhesive

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

**IDH number:** 135479

Item number:51531Region:United States

Contact information: Telephone: 860.571.5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

 Physical state:
 Gel
 HEALTH:
 \*2

 Color:
 Purple
 FLAMMABILITY:
 1

 Odor:
 Sharp
 PHYSICAL HAZARD:
 1

Personal Protection: See MSDS Section 8

WARNING: MAY BE HARMFUL IF SWALLOWED.

MAY CAUSE ALLERGIC SKIN REACTION.

CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Eyes, Lungs, Skin

**Potential Health Effects** 

**Inhalation:** May cause irritation to nose and throat.

**Skin contact:** May cause allergic skin reaction. Causes skin irritation.

**Eye contact:** Vapors may irritate eyes. Contact with eyes will cause irritation.

**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by

exposure:

Acrylic acid: Respiratory disorders. Lung disease.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Polyurethane methacrylate resin	Proprietary	60 - 100	
Polyglycol dimethacrylate	25852-47-5	10 - 30	
Silica, amorphous, fumed, crystal-free	112945-52-5	5 - 10	
Acrylic acid	79-10-7	1 - 5	
Cumene hydroperoxide	80-15-9	1 - 5	
Saccharin	81-07-2	1 - 5	
Ethylene glycol	107-21-1	0.1 - 1	
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1	

IDH number: 135479 Product name: LOCTITE® 515™ GASKET ELIMINATOR® FLANGE SEALANT PART NO. 51531

Page 1 of 5

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Wash clothing before reuse. If

symptoms develop and persist, get medical attention. Wash with soap and

water.

**Eye contact:** Get medical attention. Flush with copious amounts of water, preferably,

lukewarm water for at least 15 minutes, holding eyelids open all the time.

Ingestion: Get medical attention. Do not induce vomiting. Keep individual calm.

### 5. FIRE FIGHTING MEASURES

**Flash point:** > 93.3 °C (> 199.94 °F) None

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available

Flammable/Explosive limits - upper:

Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: None
Unusual fire or explosion hazards: None

IDH number: 135479

Hazardous combustion products: Oxides of sulfur. Oxides of carbon. Oxides of nitrogen. Irritating organic

apours.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand,

silica gel, acid binder, universal binder, sawdust). Store in a partly filled,

closed container until disposal.

## 7. HANDLING AND STORAGE

Handling: Do not breathe gas/fumes/vapor/spray. Avoid contact with eyes, skin and

clothing.

**Storage:** For safe storage, store at or below 38 °C (100.4 °F)

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Product name: LOCTITE® 515™ GASKET ELIMINATOR® FLANGE SEALANT PART NO. 51531

Page 2 of 5

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyurethane methacrylate resin	None	None	None	None
Polyglycol dimethacrylate	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Acrylic acid	2 ppm TWA (SKIN)	None	None	1 ppm TWA 3 ppm STEL (SKIN)
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Saccharin	None	None	None	None
Ethylene glycol	100 mg/m3 Ceiling Aerosol.	None	None	None
1-Acetyl-2-phenylhydrazine	None	None	None	None

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). Use an organic vapor respirator for concentrations exceeding the

Occupational Exposure Limit.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Natural rubber gloves. Butyl rubber gloves. Neoprene gloves.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Gel Color: Purple Odor: Sharp Odor threshold: Not available pH: Not applicable

< 10 mm hg (80 °F (26.7 °C)) Vapor pressure: > 300 °F (> 148.9 °C) None Boiling point/range:

Melting point/ range: Not available Specific gravity: Vapor density: 1 1

Not available

Flash point: > 93.3 °C (> 199.94 °F) None

Flammable/Explosive limits - lower: Not available Flammable/Explosive limits - upper: Not available Autoignition temperature: Not available Evaporation rate: Not available Solubility in water: Slight Partition coefficient (n-octanol/water): Not available VOC content: < 4 % (calculated)

# 10. STABILITY AND REACTIVITY

Stability: Stable

IDH number: 135479

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of sulfur. Oxides of carbon. Oxides of nitrogen. Irritating organic

vapours.

Incompatible materials: Strong oxidizing agents.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

Product name: LOCTITE® 515™ GASKET ELIMINATOR® FLANGE SEALANT PART NO. 51531

Page 3 of 5

## 11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 5,000 mg/kg (Estimated)

Acute dermal product toxicity: LD50 (rabbit) > 2,000 mg/kg

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyurethane methacrylate resin	No	No	No
Polyglycol dimethacrylate	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Acrylic acid	No	No	No
Cumene hydroperoxide	No	No	No
Saccharin	No	No	No
Ethylene glycol	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No

Hazardous components	Health Effects/Target Organs	
Polyurethane methacrylate resin	Irritant, Allergen	
Polyglycol dimethacrylate	Irritant, Allergen	
Silica, amorphous, fumed, crystal-free	Nuisance dust	
Acrylic acid	Allergen, Corrosive, Irritant, Kidney, Liver	
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen	
Saccharin	No Target Organs	
Ethylene glycol	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant,	
	Kidney, Liver, Metabolic	
1-Acetyl-2-phenylhydrazine	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity	

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

# 14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

#### **U.S. Department of Transportation Ground (49 CFR)**

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

IDH number: 135479 Product name: LOCTITE® 515™ GASKET ELIMINATOR® FLANGE SEALANT PART NO. 51531 Page 4 of 5

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Acrylic acid (CAS# 79-10-7). Cumene hydroperoxide (CAS# 80-15-9).

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm. This product contains a chemical known in the State of California

to cause cancer.

**Canada Regulatory Information** 

WHMIS hazard class:

IDH number: 135479

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 8

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: LOCTITE® 515™ GASKET ELIMINATOR® FLANGE SEALANT PART NO. 51531

Page 5 of 5