



Revision Number: 004.0

Issue date: 03/31/2011

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOC PLASTIC BONDR SYR 8P PTA
Product type: Acrylics

IDH number: 1442491
Item number: 1363118_AA0311
Region: United States

Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

Contact information:
 Telephone: 860.571.5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Paste
Color: White, Opaque
Odor: Sharp

HMIS:

HEALTH: *2
FLAMMABILITY: 3
PHYSICAL HAZARD: 1
Personal Protection: See MSDS Section 8

WARNING: FLAMMABLE LIQUID AND VAPOR.
 CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
 MAY CAUSE ALLERGIC SKIN REACTION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Causes respiratory tract irritation. May cause central nervous system effects with nausea, dizziness and headache.
Skin contact: Causes skin irritation. May cause allergic skin reaction.
Eye contact: Vapors may irritate eyes. Contact with eyes will cause irritation.
Ingestion: May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Methyl methacrylate	80-62-6	30 - 60
Polyethylene based rubber	Proprietary	10 - 30
2-Hydroxyethyl methacrylate	868-77-9	10 - 30
Methacrylic acid	79-41-4	1 - 5
Tert-butyl perbenzoate	614-45-9	1 - 5
Butyl hydroxytoluene	128-37-0	1 - 5
Talc	14807-96-6	0.1 - 1
Carbon tetrachloride	56-23-5	0.1 - 1
Hydroquinone	123-31-9	0.1 - 1

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	14 °C (57.2 °F) Setaflash Closed Cup
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
Hazardous combustion products:	Oxides of carbon. Oxides of sulfur. Hydrogen chloride. Acids. Aldehydes. Alcohols. Toxic fumes. Irritating organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material.
------------------	--

Storage:

For safe storage, store at or below 32 °C (89.6 °F)
Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Protect from direct sunlight.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methyl methacrylate	50 ppm TWA 100 ppm STEL (Sensitiser.)	100 ppm (410 mg/m3) TWA	None	50 ppm
Polyethylene based rubber	None	None	None	None
2-Hydroxyethyl methacrylate	None	None	None	3 ppm Ceiling
Methacrylic acid	20 ppm TWA	None	None	None
Tert-butyl perbenzoate	None	None	None	None
Butyl hydroxytoluene	2 mg/m3 TWA Inhalable fraction and vapor.	None	None	None
Talc	2 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	50 ppm
Carbon tetrachloride	5 ppm TWA 10 ppm STEL (SKIN)	10 ppm TWA 25 ppm Ceiling 200 ppm MAX. CONC 5 minutes in any 4 hours	None	None
Hydroquinone	1 mg/m3 TWA (Sensitiser.)	2 mg/m3 TWA	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Nitrile gloves. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Paste

Color:

White, Opaque

Odor:

Sharp

Odor threshold:

Not available

pH:

Not available

Vapor pressure:

28 mm hg (20 °C (68°F))

Boiling point/range:

> 100 °C (> 212°F)

Melting point/ range:

Not available

Specific gravity:

1.04

Vapor density:

> 1

Flash point:

14 °C (57.2 °F) Setflash Closed Cup

Flammable/Explosive limits - lower:

Not available

Flammable/Explosive limits - upper:

Not available

Autoignition temperature:

Not available

Evaporation rate: Faster than ether., (Ether = 1)
Solubility in water: Slight
Partition coefficient (n-octanol/water): Not available
VOC content: 0.3 %; 2.87 g/l

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.
Hazardous reactions: Polymerization may occur at elevated temperatures or upon depletion of inhibitor.
Hazardous decomposition products: Oxides of carbon. Oxides of sulfur. Hydrogen chloride. Acids. Alcohols. Aldehydes. Toxic fumes. Irritating organic vapours.
Incompatible materials: Oxidizing agents. Reducing agents. Acids. Bases. Free radical initiators. Peroxides. Alkali metals.
Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. Exposure to sunlight. Do not mix in batches greater than 100 grams (0.22 pounds) unless you plan to use immediately.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methyl methacrylate	No	No	No
Polyethylene based rubber	No	No	No
2-Hydroxyethyl methacrylate	No	No	No
Methacrylic acid	No	No	No
Tert-butyl perbenzoate	No	No	No
Butyl hydroxytoluene	No	No	No
Talc	No	No	No
Carbon tetrachloride	Anticipated carcinogen.	Group 2B	No
Hydroquinone	No	No	No

Hazardous components	Health Effects/Target Organs
Methyl methacrylate	Allergen, Irritant, Kidney, Liver, Mutagen, Nervous System, Respiratory
Polyethylene based rubber	No Target Organs
2-Hydroxyethyl methacrylate	Irritant, Allergen
Methacrylic acid	Corrosive, Irritant, Allergen
Tert-butyl perbenzoate	Central nervous system, Irritant, Mutagen
Butyl hydroxytoluene	Irritant, Mutagen
Talc	Irritant, Lung, Some evidence of carcinogenicity
Carbon tetrachloride	Cardiac, Central nervous system, Irritant, Kidney, Liver, Some evidence of carcinogenicity
Hydroquinone	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Immune system, Irritant, Liver, Mutagen, Skin, Thyroid

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable. D019: Carbon tetrachloride.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II
DOT Reportable quantity: Methyl methacrylate, Carbon tetrachloride

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methyl methacrylate (CAS# 80-62-6). Carbon tetrachloride (CAS# 56-23-5).

CERCLA Reportable quantity: Methyl methacrylate (CAS# 80-62-6) 1,000 lbs. (454 kg)
Carbon tetrachloride (CAS# 56-23-5) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

WHMIS hazard class: B.2, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 1,2,3,4,5,6,7,8,10,14,15

Prepared by: Rena Petrides, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.