

*Estimated N/A-Not Applicable N/R-Not Restricted N/E-Not Established

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.									
IDENTITY	PART NO.								
(As shown on Label or package) F-938 H.P. Primer					IF APPLICABLE				
SECTION I									
MANUFACTURER'S		EMERGENCY PHONE No.							
NAME Plasti Dip International, Inc.					1-800-424-9300				
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE) 3920 Pheasant Ridge Drive				REVISION #					
Blaine, MN 55449	MANUFACTURER'S PHONE No. FOR INFORMATION 1-763-785-2156								
	DATE MSDS WAS PREPARED May 13, 2010								
WAS PREPARED May 13, 2010 SECTION II - HAZARDOUS INGREDIENTS INFORMATION. All Health Hazards which comprise 1% or greater of the composition and all carcinogene									
if 0.1% of the composition or greater.			ann mazarus which compi	list 170 of great	i of the compo	sition and an carcinogens			
HAZARDOUS COMPONENTS CHEMIC	AL and	% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS			
IDENTITY AND COMMON NAME		OPTIONAL)	CABINO.	PEL	TLV	RECOMMEND			
Toluene	(0) (1	83-87	108-88-3	200ppm	50ppm	Skin			
Xylene		6-10	1330-20-7	100ppm	100ppm	None			
Ethylbenzene		1-3	100-41-4	100 ppm	100 ppm	None			
		-							
SECTION III - PHYSICAL / CHEMICAL	CHARACTERI	STICS							
BOILING	SPECIFIC GE		=1)	APPROXIMA	TE WEIGHT	PER GALLON (LBS)			
POINT 232 - 279°F	0.86 - 0.88			7.23					
VAPOR PRESSURE	VAPOR DENSITY			EVAPORATION RATE					
22 mmHg @ 20°C	(AIR = 1) Heavier than air			(BUTYL ACETATE =1) > 1.0					
SOLUBILITY IN WATER	% VOLATIL	% VOLATILE 95%			OTHER				
Insoluble	VOC LBS./GAL 6.87			(IF ANY) None					
APPEARANCE									
AND ODOR Characteristic solvent odor - clear liquid									
SECTION IV-FIRE AND EXPLOSION HA	AZARD DATA								
FLASH POINT 45°F		FLAMMA	FLAMMABLE LIMITS			UEL			
(METHOD USED) TCC				1.0		7.0			
EXTINGUISHING									
MEDIA Carbon Dioxide, Dry Chemical, or Foam									
SPECIAL FIRE									
FIGHTING PROCEDURES Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.									
UNUSUAL FIRE AND									
EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity.									
HAZARDOUS PRODUCTS FORMED BY									
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide, Hydrogen Chloride and organic hydrocarbons. EXPLOSIVE LIMITS									
(% BY VOLUME IN AIR) 1.0 – 7.0									
(70 BT VOLUME IN AIR) 1.0 - 7.0 SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION									
HAZARD RATING National Fire Protection Association (NFPA)									
4-EXTREME	National File Flotection Association (NFFA)								
3-HIGH			FIRE 3 REACTIVITY 0.						
2-MODERATE			· <u>· ·</u>						
1-SLIGHT									
0-INSIGNIFICANT	HEALTH 2 SPECIAL HAZARDS None .								
**SEE SECTION IV									

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



STABILITY	UNSTAI	BLE	STABLE X	CONDITIONS TO	CONDITIONS TO AVOID Temperatures over 350°F for over 10 minutes.			
INCOMPATIBILITY Oxidizing Materials								
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide, Hydrogen Chloride, and other organic hydrocarbons.								
HAZARDOUS			Y OCCUR	CONDITIONS TO	CONDITIONS TO AVOID			
POLYMERIZATION			LL NOT OCCUR X		None			
SECTION VII - HEALTH HAZARD DAT								
ROUTES OF ENTRY		INHALATION? Yes SKIN? Yes INGESTION? Yes EYES? Yes						
HEALTH	ACUTE	X	See Signs and Symptoms of Expe	osure below.				
HAZARDS	CHRONIC	X						
CARCINOGENICITY: Eth ylbenzene (IARC 2B)								
SIGNS AND SYMPTOMS OF		Inho	Inhalation: Headache, nausea, and irritation of nose, throat and lungs. Skin: Irritation upon repeat or					
EXPOSURE			prolonged contact. Eyes: Slightly irritation to eyes.					
LAI OSUKE		pion	nged contact. Lyes. Sugnity inta	ttion to cycs.				
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE None known								
	OID GENER		NGGNATIATED DI EM OSCI					
EMERGENCY AND		Inge	stion: Contact Physician or Poison	Control Immediately	ν.			
			Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary.					
PROCEDURES		-	Contact: Flush with large amounts					
		Skin	: Wash with soap and water.					
SECTION VIII - PRE	CAUTIONS F	OR S.	AFE HANDLING AND USE					
STEPS TO BE TAKEN			Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers.					
IN CASE MATERIAL IS			Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material					
RELEASED OR SPII	LED	to da	to dam or contain spills. If large spill, notify appropriate state and local agencies.					
WASTE DISPOSAL	METHODS	Disp	ose of product in accordance with lo	ocal, county, state an	d federal regulations.			
		17		G	1			
PRECAUTIONS TO BE			Keep away from sparks, flame and heat sources. Store in cool ventilated area.					
TAKEN IN HANDLING		Avoid contact with eyes. Keep container closed. Use with adequate ventilation. Avoid inhalation of vapors						
AND STORAGE and personal contact with liquid product. Use good personal hygiene practices.								
OTHER Keep container closed when not in use. All containers should be disposed in an environmentally safe manner				ld be disposed in an environmentally safe manner				
OTHER Reep contained closed when not in use. An containers should be disposed in an environmentary safe manner PRECAUTIONS accordance with governmental regulations.				a be disposed in an environmentally sure mainter				
SECTION IX - CONTROL MEASURES								
					PROTECTIVE GLOVES			
use a Respirator with appropriate NIOSH approved cartridge or supplied air equipi					Rubber gloves			
				•	SPECIAL None			
MECHANICAL (GENERA			ENERAL) To maintain exposure b	elow PEL's.	OTHER None			
EYE PROTECTION					OTHER PROTECTIVE CLOTHING OR EQUIPMENT			
Chemical splash goggles or approved eye protection. Chemical Apron/Eye bath/Safety shower								
WORK HYGIENIC PRACTICES Wash thoroughly after handling.								
SECTION X - TRANSPORTATION INFORMATION (Optional)								
DOT PROPER SHIPPING NAME Coating Solution					DOT HAZARD CLASS 3			
DOT UN NUMBER UN 1139					DOT PACKING GROUP II			
IATA PROPER SHIPPING NAME Coating Solution			ag Solution		IATA HAZARD CLASS 3			
IATA UN NUMBER UN 1139 IATA PACKING GROUP II								
SECTION XI - 313 SUPPLIER NOTIFICATION								
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight).								
EMERGENCY PLAN Toluene, Xylene, and E		UNIN	IUMITY KIGHT - IU-KNUW AU	.1 OF 1980, 40 CFI	\times 312, (see table on page 1 for CAS # and percent by weight).			
		NTAP	NS A CHEMICAL KNOWN TO '	THE STATE OF C	ALIFORNIA TO CAUSE CANCER AND BIRTH			
DEFECTS, OR OTH								

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Michael N Hindin

THE INFORMATION PROVIDED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM ITS USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND THE VENDORS CONTROL AND SINCE SUBSEQUENT DATA MAY SUGGEST MODIFICATION OF THE INFORMATION. VENDOR ASSUMES NO RESPONSIBILITY FOR THE RESULTS OF ITS USE.