## Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/24/2012	acc. to 150/DIS 11014	Revised On 01/24/2012	
1 Identification of the sub	stance and manufacturer		
Trade name: Product code: Manufacturer/Supplier:	SPRAY GLO FLUORESCENT YELLOW 0000161619 Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com	CUR	
Emergency telephone			
number:	CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*		
2 Composition/informatio	n en ingradiente		
Chemical Description:	This product is a mixture of the substances listed below with nonhazardous add	ditions	
Dangerous components:			
74-98-6 propane		18.83%	
64742-47-8 Mineral Spirits		11.88%	
106-97-8 n-butane		11.06%	
110-19-0 isobutyl acetate		7.74%	
64742-89-8 VM&P Naphtha		5.98%	
64742-94-5 Solvent naptha	heavy aromatic	4.55%	
<b>3 Hazards identification</b>			
Hazard Information for people and the			
environment:	Extremely flammable liquid and vapor in a pressurized container. Keep awa	av from heat sparks and	
	fame. Has narcotizing effect.	ay nom neut, spants, and	
Risk phrases:	Extremely flammable.		
Safety phrases:	Keep out of the reach of children.		
	Keep away from sources of ignition - No smoking. Do not empty into drains, dispose of this material and its container at ha collection point If swallowed, seek medical advice immediately and show this container or labe Use only in well-ventilated areas.	·	
Effects of chronic overexposure:	May cause permanent brain and nervous system damage. Repeated overe: kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inh harmful or fatal.	xposure can also damage aling the contents may be	
NFPA ratings (0 - 4):	Health- 1 Fire- 3 Reactivity- 3		
HMIS-ratings (0 - 4):	Health- 1 Flammability- 3 Physical Hazard- 3		
4 First aid measures			
After inhalation: After skin contact: After eye contact: After swallowing:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doc Contact physician or poison control center.	ctor.	
5 Firefighting measures			
Extinguishing agents:	CO2, sand, extinguishing powder, or water spray. Fight larger fires with water	r spray or alcohol resistant	
Special hazards:	foam. No further relevant information available.		
Protective equipment:	No special measures required.		
6 Accidental release measures			
Personal precautions,			
protective equipment and emergency procedures	Wear protective equipment. Keep unprotected persons away.		
Environmental precautions: Methods and material for	Do not allow product to reach sewage systems or ground water.		
containment and cleaning up:	Ensure adequate ventilation.		
		USA – (Contd. on page 2)	

(Contd. on page 2)

## Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/24/2012

Trade name: SPRAY GLO FLUORESCENT YELLOW

	(Contd. of page 1)
7 Handling and storage	
	Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic
Storage requirements:	discharges. discharges. discharge regulations. Consult with your local authorities.
9 Experies controls/pero	and protection
8 Exposure controls/pers	ues that require monitoring at the workplace:
74-98-6 propane	ues that require monitoring at the workplace.
PEL 1800 mg/m³, 1000 ppr REL 1800 mg/m³, 1000 ppr TLV Varies mg/m³, 1000 pp	n
106-97-8 n-butane	
REL 1900 mg/m³, 800 ppm TLV Varies mg/m³, 1000 pp	m
110-19-0 isobutyl acetate	
PEL 700 mg/m <sup>3</sup> , 150 ppm REL 700 mg/m <sup>3</sup> , 150 ppm TLV 713 mg/m <sup>3</sup> , 150 ppm	
Hygienic protection: Breathing equipment:	Wash hands after use.
Breathing equipment.	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.
Eye protection:	Tightly sealed goggles
9 Physical and chemical p	
Odor:	Aromatic
pH-value: Boiling point:	Not determined. -44°C (-47 °F)
Flash point:	-19°C (-2 °F)
Flammability (solid, gaseo	
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.
Lower Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 0.5 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor Pressure: Specific Gravity:	40 PSI, 2750 hPa Botwoon 0.77 and 0.85 (Water equals 1.00)
VOC content:	Between 0.77 and 0.85 (Water equals 1.00) 549.1 g/l / 4.58 lb/gl
VOC content (less exempt	solvents): 60.6 %
Water: MIR Value:	12.6 % 0.91
Solids content:	26.6 %
Other information	No further relevant information available.
10 Stability and reactivity	
10 Stability and reactivity Conditions to avoid:	Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
Hazardous	
decomposition:	No dangerous decomposition products known.
11 Toxicological information	an a
Skin effects:	No irritant effect.
Eye effects:	No irritating effect.
Sensitization:	No sensitizing effects known.
12 Ecological information	
Aquatic toxicity:	Hazardous for water, do not empty into drains.
Other information:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's),
	perfluorocarbons (PFC's), or chlorinated solvents.

Printing date 01/24/2012

## Trade name: SPRAY GLO FLUORESCENT YELLOW

Revised On 01/24/2012

(Contd. of page 2)

13 Disposal considerations         DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact.         Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.         Recommendation:       Completely empty cans should be recycled.			
14 Transport information UN-Number DOT Class Marine pollutant: EMS Number: Packaging Group:	UN1950 Consumer Commodity ORM-D AEROSOLS, flammable 2.1 No F-D,S-U 		
None of the ingredients in SARA Section 313 (Spec	mely hazardous substances): this product are listed. ific toxic chemical listings):		
100-41-4 ethyl benzene	All ingredients are listed. This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. chemicals known to cause cancer:		
Group 2B: The ingredient i	s probably carcinogenic to humans. s possibly carcinogenic to humans. There is limited evidence of carcinogenicity. s unclassifiable as to its carcinogenicity to humans.	D	
ACGIH: 110-19-0 isobutyl acetate NIOSH:		44	
<ul> <li>16 Other information         This product was manufac         The information on this sl         product features and shall         Contact:         Abbreviations and         acronyms:         </li> </ul>	tured in the U.S.A. heet is based on our present knowledge. However, this shall not constitute a guarantee for any spec not establish a legally valid contractual relationship. Regulatory Affairs MDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) ISO: International Organization for Standardization EPA: Environmental Protection Agency IARC: International Agency for the Research of Cancer NIOSH: National Institute for Occupational Safety and Health	>ific	
	TSCA: Toxic Substances Control Act CPSC: Consumer Product Safety Commission		