Finished Product



Date Issued: 10/22/2002 MSDS No: ms1672-A Date Revised: 12/07/2009 Revision No: 9

Envi-Ro-Tech Freezer

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Envi-Ro-Tech Freezer PRODUCT DESCRIPTION: HFC-134a PRODUCT CODE: 1672/CAN/EUR-10S, 15S CHEMICAL FAMILY: Hydrofluorocarbons ACTIVE INGREDIENT(S): 1,1,1,2-Tetrafluoroethane

MANUFACTURER

24 HR. EMERGENCY TELEPHONE NUMBERS

Techspray, L.P. CH 1001 N.W. 1st Street CANUTE P.O. Box 949 Amarillo TX 79107 Emergency Contact: Chemtrec Product Stewardship: 1-800-858-4043 Service Number: 1-800-858-4043

CHEMTREC (US Transportation) :(800) 424 - 9300 CANUTEC (Canadian Transportation) :(613) 996 - 6666 Emergency Phone :(800) 858 - 4043

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear, Colorless, Volatile Liquid

IMMEDIATE CONCERNS: Warning! High concentrations of vapor can reduce oxygen available for breathing. Harmful if inhaled. May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products.

POTENTIAL HEALTH EFFECTS

EYES: Liquid contact can cause irritation, which may be severe.

- **SKIN:** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).
- **INHALATION:** High concentrations in immediate area can displace oxygen and can cause dizziness, unconsciousness, and possibly death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Can cause severe eye irritation.

SKIN: Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold" burn).

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

ACUTE TOXICITY: Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Finished Product



Date Issued: 10/22/2002 MSDS No: ms1672-A Date Revised: 12/07/2009 Revision No: 9

Envi-Ro-Tech Freezer

Chemical Name	Wt.%	CAS	EINECS
1,1,1,2-Tetrafluoroethane	100	811-97-2	212-337-0

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

- **SKIN:** In case of cold burns (frostbite) caused by rapidly expanding gas or vaporizing liquids, get medical attention promptly.
- **INGESTION:** Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.
- **INHALATION:** Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
- **NOTES TO PHYSICIAN:** Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: Not Applicable

FLAMMABLE LIMITS: None*

AUTOIGNITION TEMPERATURE: > 750°C (1382°F)

FLAMMABLE CLASS: Not Applicable

FLAME PROPAGATION OR BURNING RATE OF SOLIDS: Not Applicable

EXTINGUISHING MEDIA: As appropriate for combustibles in area.

EXPLOSION HAZARDS: This product is not flammable at ambient temperatures and atmospheric pressure. However, this material may become combustible when mixed with air under pressure and exposed to strong ignition sources.

FIRE FIGHTING PROCEDURES: Use water spray to cool containers.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressuredemand, (MSHA/NIOSH approved or equivalent) and full protective gear.

COMMENTS: *Based on ASHRAE Standard 34 with match ignition.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Isolate hazard area. Keep unnecessary and unprotected personnel from entering.

Finished Product



Date Issued: 10/22/2002 MSDS No: ms1672-A Date Revised: 12/07/2009 Revision No: 9

Envi-Ro-Tech Freezer

RELEASE NOTES: Spills and releases may have to be reported to Federal and/or local authorities.

7. HANDLING AND STORAGE

HANDLING: Follow standard safety precautions for handling and use of compressed gas cylinders.

STORAGE: Store in a cool place in original container and protect from sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
	OSHA PEL		ACGIH TLV		SupplierOEL		
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1,1,1,2-Tetrafluoroethane	TWA	NE		NE		1,000 ppm ^[1]	[1]
OSHA TABLE COMMENTS: 1. * (AEL)=Acceptable Exposure Limit as established by the manufacture							

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles) and a face shield.

SKIN: Skin contact with liquid may cause frostbite. General work clothing and gloves (leather) should provide adequate protection. If prolonged contact with the liquid or gas is anticipated, insulated gloves constructed of PVA, neoprene or butyl rubber should be used. Any contaminated clothing should be promptly removed and washed before reuse.

RESPIRATORY: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Boiling Point (°C)	Freezing Point (°C)	Solubility in Water	Specific Gravity
1,1,1,2-Tetrafluoroethane	-26.4	-101	NEGLIGIBLE	1.21

PHYSICAL STATE: Gas

ODOR: Faint ethereal odor

Finished Product



Date Issued: 10/22/2002 MSDS No: ms1672-A Date Revised: 12/07/2009 Revision No: 9

Envi-Ro-Tech Freezer

pH: Neutral

PERCENT VOLATILE: 100 at 20°C (68°F)

VAPOR PRESSURE: 85.8 psi at 21.1°C (70°F)

VAPOR DENSITY: 3.5 (Air=1)

BOILING POINT: -26.2°C (-15.1°F)

FREEZING POINT: -101°C (-149.8°F)

FLASHPOINT AND METHOD: Not Applicable

SOLUBILITY IN WATER: Negligible

EVAPORATION RATE: > 1 (CCL4=1)

SPECIFIC GRAVITY: 1.220 (water=1) at 20°C (68°F)

MOLECULAR WEIGHT: 102

(VOC): g/L (non-exempt VOC) Notes: Exempt

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable.

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Stable. However, may decompose if heated.

HAZARDOUS DECOMPOSITION PRODUCTS: Whem exposed to high temperatures or flames this product may form hydrochloric and hydrofluoric acids - possibly carbonyl halides.

INCOMPATIBLE MATERIALS: Chemically active metals: potassium, calcium, powdered aluminum, magnesium and zinc.

11. TOXICOLOGICAL INFORMATION

ACUTE

Cher	nical Name	INHALATION LC ₅₀ (rat)
1,1,1	,2-Tetrafluoroethane	> 500000 ppm

Finished Product



Date Issued: 10/22/2002 MSDS No: ms1672-A Date Revised: 12/07/2009 Revision No: 9

Envi-Ro-Tech Freezer

CHRONIC: Chronic NOEL - 10,000 ppm

SUBCHRONIC: Subchronic inhalation (rat) NOEL - 50,000 ppm

CARCINOGENICITY

Chemical Name	NTP	IARC	OSHA
	Status	Status	Status
1,1,1,2-Tetrafluoroethane	NOT	NOT	NOT
	LISTED	LISTED	LISTED

SENSITIZATION: Cardiac sensitization threshold (dog) 80,000 ppm. NOEL - 50,000 ppm.

TERATOGENIC EFFECTS: Teratogenic NOEL (rat and rabbit) - 40,000 ppm

MUTAGENICITY: Collective data indicate non-mutagenic.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Degradability (BOD): This material is a gas at room temperature; therefore, it is unlikely to remain in water.

DISTRIBUTION: Octanol Water Partition Coefficient: Log P=1.06

13. DISPOSAL CONSIDERATIONS

GENERAL COMMENTS: 1,1,1,2-tetrafluoroethane is subject to U.S. Environmental Protection Agency Clean Air Act Regulations, Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: CONSUMER COMMODITY, ORM-D, DOT-SP 10232

PRIMARY HAZARD CLASS/DIVISION: 9

UN/NA NUMBER: NA

PACKING GROUP: NA

NAERG: #12

OTHER SHIPPING INFORMATION: Must have a copy of the DOT-SP-10232 with each shipment.

SPECIAL SHIPPING NOTES: Domestic Shipments Only. For International shipments use 1,1,1,2-Tetrafluoroethane, UN3159, 2.2; Pkg. Instr. 200.; Authorization: DOT-SP 10232.;**NOTE:** Copy of the Exemption is required with all shipments.; HAZARD LABEL: Non-Flammable Gas.; ["LTD QTY of class 2" when <120mL (5 oz)]

ROAD AND RAIL (ADR/RID)

KEMLER NUMBER: UN3159

Finished Product



Date Issued: 10/22/2002 MSDS No: ms1672-A Date Revised: 12/07/2009 Revision No: 9

Envi-Ro-Tech Freezer

HAZARD CLASS: 2.2

AIR (ICAO/IATA)

SHIPPING NAME: CONSUMER COMMODITY, ORM-D-AIR, DOT-SP 10232

UN/NA NUMBER: ID8000

PRIMARY HAZARD CLASS/DIVISION: 9

PACKING GROUP: NA

VESSEL (IMO/IMDG)

SHIPPING NAME: 1,1,1,2-Tetrafluoroethane

UN/NA NUMBER: UN3159

PRIMARY HAZARD CLASS/DIVISION: 2.2

PACKING GROUP: NA

LIMITED QUANTITY: 120 mL

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: IMMEDIATE / PRESSURE

PRESSURE GENERATING: Yes ACUTE: Yes

313 REPORTABLE INGREDIENTS: Not considered a SARA 313 "Toxic Chemical".

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Releases to air, land, or water which exceed the RQ must be reported to the National Response Center [(800)424-8802] and to your Local Emergency Planning Committee.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
1,1,1,2-Tetrafluoroethane	811-97-2

TSCA REGULATORY: This product is listed on the TSCA Inventory.

CLEAN AIR ACT

Chemical Name	Wt.%	CAS
1,1,1,2-Tetrafluoroethane	100	811-97-2

CALIFORNIA PROPOSITION 65: This product does not contain any chemicals known to the State of California to cause cancer.

CANADA

WHMIS CLASS: Class A, Class D2B.

Finished Product



Date Issued: 10/22/2002 MSDS No: ms1672-A Date Revised: 12/07/2009 Revision No: 9

Envi-Ro-Tech Freezer

DOMESTIC SUBSTANCE LIST (INVENTORY): All components of this product are listed on the Canadian DSL.

GENERAL COMMENTS: 1,1,1,2-tetrafluoroethane is subject to U.S. Environmental Agency Clean Air Act Regulations, (40CFR Part 82).

COMMENTS WARNING: Contains 1,1,1,2-tetrafluoroethane (HFC-134a), a greenhouse gas which may contribute to global warming.


16. OTHER INFORMATION

APPROVED BY: Dana M. Morelos TITLE: Chemist

PREPARED BY: Steve Cook

REVISION SUMMARY: Revision #: 9. This MSDS replaces the June 23, 2009 MSDS., Any changes in information are as follows: In Section 15: EEC Risk Phrase CodesIn Section 16: General Statements





DATA SOURCES: Code of Federal Regulations (CFR) The Sigma-Aldrich Library of Regulatory and Safety Data OSHA Hazard Communication Standard (29CFR1910.1200) Various Federal, State and Local Regulations

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither Tech Spray, L.P., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.