

MATERIAL SAFETY DATA SHEET



J.T.Bake

Material name	HYDROCHLORIC ACID, 33-40%	
Version #	05	
Revision date	06-25-2010	
CAS #	Mixture	
Product Codes	J.T.Baker: 5367, 5537, 5575, 5800, 5814, 5821, 5839, 5861, 5862, 5894, 5962, 5963, 5972, 5994, 6900, 7831, 9165, 9529, 9530, 9534, 9535, 9536, 9538, 9539, 9540, 9544, 9548, 9551, 9625, IM2612 Mallinckrodt: 2062, 2515, 2612, 2624, 2626, 3861, 5583, 5587, H611, H613, H616, H987, H992, H999, V078, V628	
Synonym(s)	Muriatic acid * hydrogen chloride, aqueous	
Manufacturer Address	Mallinckrodt Baker, Inc. 222 Red School Lane Phillipsburg, NJ 08865 US	
Customer Service	800-582-2537	
24 Hour Emergency	908-859-2151	
Chemtrec	800-424-9300	
2. Hazards Identification		
Emergency overview	DANGER POISON Corrosive. Causes skin and eye burns. May be fatal if swallowed or inhaled. Prolonged exposure may cause chronic effects.	
OSHA regulatory status	This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).	
Potential health effects		
Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.	
Eyes	Risk of serious damage to eyes. Do not get this material in contact with eyes. Causes eye burns.	
Skin	Causes skin burns. Do not get this material in contact with skin.	
Inhalation	Causes burns. Prolonged inhalation may be harmful. May cause lung damage. Do not breathe dust/fume/gas/mist/vapors/spray.	
Ingestion	Components of the product may be absorbed into the body by ingestion. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract. Ingestion of this product may cause nausea, vomiting and diarrhea. Do not ingest.	
Target organs	Eyes. RESPIRATORY SYSTEM. Skin. Lungs.	
Signs and symptoms	Contact with this material will cause burns to the skin, eyes and mucous membranes. Symptoms are prostration, gasping, pallor, and uncoordinated movements. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Irritation of nose and throat.	
Potential environmental effects	Components of this product are hazardous to aquatic life. May cause long-term adverse effects in the environment.	

3. Composition / Information on Ingredients

Hazardous components	CAS #	Percent
HYDROGEN CHLORIDE	7647-01-0	33 - 40
New beyondours common ante	CAC #	Descent
Non-hazardous components	CAS #	Percent

First aid procedures	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Skin contact	Remove and isolate contaminated clothing and shoes. Immediately flush skin with plenty of water. Get medical attention immediately. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention immediately.
Ingestion	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting without advice from poison control center. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Rinse mouth thoroughly. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Notes to physician	In case of shortness of breath, give oxygen. Keep victim warm.
General advice	Immediate medical attention is required. In case of shortness of breath, give oxygen. Keep victim warm. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire Fighting Measures

of the thighting medeal ee		
Flammable properties	The product is not flammable. No unusual fire or explosion hazards noted.	
Extinguishing media Suitable extinguishing media	Water.	
Protection of firefighters		
Protective equipment and precautions for firefighters	In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out.	
Specific methods	In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.	
6. Accidental Release Mea	Isures	
Personal precautions	Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Keep out of low areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep upwind.	
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.	
Methods for containment	Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewer, basements or confined areas.	
Methods for cleaning up	Should not be released into the environment.	
	Large Spills: Dike far ahead of spill for later disposal. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.	
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece).	
	Never return spills in original containers for re-use. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination.	
	J. T. Baker NEUTRASORB® acid neutralizers are recommended for spills of this product.	

7. Handling and Storage	
Handling	Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get this material on clothing. Do not use in areas without adequate ventilation. Avoid prolonged exposure. Wash thoroughly after handling. Handle and open container with care. Use caution when combining with water; DO NOT add water to acid, ALWAYS add acid to water while stirring to prevent release of heat, steam and fumes.
Storage	Store in a well-ventilated place. Keep container tightly closed. Keep out of the reach of children. Use care in handling/storage. Keep away from food, drink and animal feedingstuffs.

8. Exposure Controls / Personal Protection

Occupational exposure limits				
ACGIH				
Components		Туре	Value	
HYDROGEN CHLORIDE	(7647-01-0)	Ceiling	2.0000 ppm	
U.S OSHA				
Components		Туре	Value	
HYDROGEN CHLORIDE	(7647-01-0)	Ceiling	5.0000 ppm 7.0000 mg/m3	
Engineering controls	should be matche or other engineer	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
Personal protective equipmer	nt			
Eye / face protection	• •	Do not get in eyes. Chemical goggles are recommended. Wear safety glasses with side shields (or goggles). Face-shield. Provide eyewash station and safety shower.		
Skin protection	splash goggles ar resistant clothing.	Do not get this material in contact with skin. Do not get this material on clothing. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent). Wear appropriate chemical resistant clothing. Chemical resistant gloves. Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations.		
Respiratory protection		Do not breathe dust/fume/gas/mist/vapors/spray. Wear positive pressure self-contained breathing apparatus (SCBA).		
General hygeine considerations	clothing. When us	Do not get in eyes. Do not get this material in contact with skin. Do not get this material on clothing. When using, do not eat, drink or smoke. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice.		
General	•	Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations.		

9. Physical & Chemical Properties

Appearance	Clear.		
Color	Colorless.		
Odor	Pungent.	Pungent.	
Odor threshold	Not available.	Not available.	
Physical state	Liquid.		
Form	Liquid.	Liquid.	
рН	0.1 - 2.02	0.1 - 2.02	
Melting point	-101.2 °F (-74 °C)	-101.2 °F (-74 °C)	
Freezing point	Not available.		
Boiling point	217.4 °F (103 °C) estimated	217.4 °F (103 °C) estimated	
Flash point	Not available.		

Evaporation rate	Not available.
Flammability	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not available.
Vapor pressure	0 hPa estimated
Vapor density	Not available.
Specific gravity	1.05 estimated
Relative density	Not available.
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Percent volatile	63.5 % estimated
Molecular formula	HCI

10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions.
Conditions to avoid	Reacts violently with strong alkaline substances. This product may react with reducing agents. Do not mix with other chemicals.
Incompatible materials	Incompatible with bases. Amines. Acids. This product may react with reducing agents. Contact with metals may evolve flammable hydrogen gas.
Hazardous decomposition products	Hydrogen chloride. Chlorine. May decompose upon heating to produce corrosive and/or toxic fumes.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

11. Toxicological Information

Test Results
Acute Dermal LD50 Mouse: 3970 mg/kg estimated
Acute Inhalation LC50 Mouse: 3036 mg/l estimated
Acute Inhalation LC50 Rat: 8559 mg/l estimated
Acute Oral LD50 Rabbit: 2466 mg/kg estimated
Test Results
Acute Dermal LD50 Mouse: 1449 mg/kg
Acute Inhalation LC50 Mouse: 1108 mg/l 1.00 Hours
Acute Inhalation LC50 Rat: 3124 mg/l 1.00 Hours
Acute Oral LD50 Rabbit: 900 mg/kg

* Estimates for product may be based on additional component data not shown.

Acute effects	Causes burns.
Local effects	Causes burns.
Chronic effects	Hazardous by OSHA criteria. Prolonged exposure may cause chronic effects.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

ACGIH Carcinogens			
HYDROGEN CHLORIDE (CAS 7647-01-0) IARC Monographs. Overall Evaluation of Carcinogenicity HYDROGEN CHLORIDE (CAS 7647-01-0)		A4 Not classifiable as a human carcinogen.	
		3 Not classifiable as to carcinogenicity to humans.	
Skin corrosion/irritation	Hazardous by OSHA criteria		
Epidemiology	Not available.		
Neurological effects	Not available.		
12. Ecological Information			
Ecotoxicological data			
Product		Test Results	
HYDROCHLORIC ACID, 33-4	10% (Mixture)	LC50 Fish: 773 mg/l 96.00 Hours estimated	
Components		Test Results	
HYDROGEN CHLORIDE (764	47-01-0)	LC50 Western mosquitofish (Gambusia affinis): 282 mg/l 96.00 Hours	
* Estimates for product m	ay be based on additional compone	ent data not shown.	
Ecotoxicity		Components of this product are hazardous to aquatic life. Because of the low pH of this product, would be expected to produce significant ecotoxicity upon exposure to aquatic organisms and	
Environmental effects	Harmful to aquatic organisms	S.	
Persistence and degradability	Not available.		
13. Disposal Considerat	tions		
Waste codes	D002: Waste Corrosive mate	erial [pH <=2 or =>12.5, or corrosive to steel]	
Disposal instructions	Incinerate the material under	Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Dispose in accordance with all applicable regulations.	
14. Transport Informatio	n		
DOT			
Basic shipping requireme	ents:		
UN number	UN1789		
Proper shipping name	HYDROCHLORIC ACID		
Hazard class	8		
Packing group Additional information:	II		
ERG number	157		
ATA			
Basic shipping requireme	ents:		
UN number	1789		
Proper shipping name	HYDROCHLORIC ACID		
Hazard class	8		
Packing group	II		
MDG			
Basic shipping requireme	ents:		
	1780		

UN number	1789
Proper shipping name	HYDROCHLORIC ACID
Hazard class	8
Packing group	II

CORROSIVE		
8	8	8
DOT	IATA	IMDG

15. Regulatory Information

US federal regulations	This product is a "Hazardous Chemical" as defined Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Invento	
US EPCRA (SARA Title III) S	ection 302 - Extremely Hazardous Spill: Reportable q	uantity
HYDROGEN CHLORID	(CAS 7647-01-0) 5000 LBS	
US EPCRA (SARA Title III) S	ection 302 - Extremely Hazardous Substance: Thresh	old Planning Quantity
HYDROGEN CHLORID	. ,	
	ection 313 - Toxic Chemical: De minimis concentratio	n
HYDROGEN CHLORID		
• • •	ection 313 - Toxic Chemical: Listed substance	
HYDROGEN CHLORID	X ,	
CERCLA (Superfund) reportable HYDROGEN CHLORIDE: 50		
Superfund Amendments and Re	authorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	
Section 311 hazardous chemical	Yes	
Inventory status		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS	S) Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China	a (IECSC) Yes
Europe	European Inventory of Existing Commercial Chemic Substances (EINECS)	cal Yes
Europe	European List of Notified Chemical Substances (EL	.INCS) No
Japan	Inventory of Existing and New Chemical Substance	es (ENCS) Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Su (PICCS)	ibstances Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all compo	nents of this product comply with the inventory requirements	s administered by the governing country(s)
State regulations	This product does not contain a chemical known to defects or other reproductive harm.	the State of California to cause cancer, birth

US - New Jersey Community RTK (EHS Survey): Reportable threshold		
HYDROGEN CHLORIDE (CAS 7647-01-0) 500 LBS		
US - Pennsylvania RTK - Hazardous Substances: Listed substance		
HYDROGEN CHLORIDE	E (CAS 7647-01-0) Listed.	
Saf-T-Data	Health: 3 - Severe (Poison) Flammability: 0 - None Reactivity: 2 - Moderate Contact: 4 - Extreme (Corrosive) Lab Protective Equip: D - GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES Storage Color Code: W - White (Corrosive)	
16. Labeling Info		
Label Hazard Warning	DANGER POISON Corrosive. Causes skin and eye burns. May be fatal if swallowed or inhaled. Prolonged exposure may cause chronic effects.	
Label Precautions	Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Keep container closed. Wash thoroughly after handling.	
Label First Aid	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. Immediately flush skin with plenty of water. Get medical attention. If gas/fume/vapor/dust/mist from the material is inhaled, remove the affected person immediately to fresh air. Get medical attention immediately. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting without advice from poison control center. Do not use mouth-to-mouth method if victim ingested the substance.	
17. Other Information		
NFPA ratings	Health: 3 Flammability: 0 Instability: 1	
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.	
Issue date	06-25-2010	
This data sheet contains changes from the previous version in section(s):	Fire Fighting Measures: Specific hazards arising from the chemical	