SUPPLIER



MATERION

MATERIAL SAFETY DATA SHEET

GENERATED 03/15/2011, REVISION 01/24/1995, DATE CREATED 03/26/1991

SECTION I - PRODUCT IDENTIFICATION Lutetium metal, pieces					
PRODUCT NAME:	Lutetium metal, pieces				
PRODUCT CODE:	L-MSDS0085				
REFERENCE #:	7439-94-3				
MANUFACTURER INFORMATION					
COMPANY NAME:	Materion Advanced Chemicals Inc	5.			
	1316 W. St. Paul Avenue				
	Milwaukee, WI 53233				
EMERGENCY CONTACT:	CHEMTREC	(800)424-9300			
ALTERNATE EMERGENCY CONTACT:	Materion Advanced Chemicals Inc	c. (414)289-9800			
CHEMICAL FAMILY:	Metal				
CAS NUMBER:	7439-94-3				
FORMULA:	Lu				
MOLECULAR WEIGHT:	174.97				
<u>SYNONYMS</u>					

Lutetium metal; Cassiopeium

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION Lutetium metal, pieces					
Hazardous Components (Chemical Name)	CAS #	Concentration	OSHA PEL	ACGIH TLV	Other Limits
Lutetium metal	7439-94-3	0.0 -100.0 %	NE	NE	NE

http://materion.com/MSDS/m000969.htm (1 of 6) [2/29/2012 9:44:59 AM]

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS Lutetium metal, pieces

1	
PHYSICAL STATES:	[] Gas [] Liquid [X] Solid
MELTING POINT:	1663.00 C
BOILING POINT:	3402.00 C
SPECIFIC GRAVITY (WATER = 1):	8.84 gm/cc
VAPOR PRESSURE (VS. AIR OR MM HG):	NA
VAPOR DENSITY (VS. AIR = 1):	NA
EVAPORATION RATE (VS BUTYL ACETATE=1):	NA
SOLUBILITY IN WATER:	NE
SOLUBILITY NOTES	
PERCENT VOLATILE:	N.A.
APPEARANCE AND ODOR	

Silver metallic pieces, no odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA Lutetium metal, pieces

FLASH PT: EXPLOSIVE LIMITS: EXTINGUISHING MEDIA N.A. Method Used: Unknown LEL: NA UEL: NA

USE: Not applicable. Use suitable extinguishing agent for surrounding materials and type of fire.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

UNUSUAL FIRE AND EXPLOSION HAZARDS

When heated to decomposition, lutetium metal may emit toxic fumes.

HAZARDOUS COMBUSTION PRODUCTS

http://materion.com/MSDS/m000969.htm (2 of 6) [2/29/2012 9:44:59 AM]

SECTION V - REACTIVITY DATA Lutetium metal, pieces

<	STABILITY: Unstable [] Stable [X]
(CONDITIONS TO AVOID - INSTABILITY
ľ	lone
	NCOMPATIBILITY - MATERIALS TO AVOID
<.	Strong acids, strong oxidizing agents and halogens
ŀ	HAZARDOUS DECOMPOSITION OR BYPRODUCTS
ſ	None recorded
•	
	HAZARDOUS POLYMERIZATION: Will occur [] Will not occur [X]
(CONDITIONS TO AVOID - HAZARDOUS POLYMERIZATION
Г	Jone

SECTION VI - HEALTH HAZARD DATA Lutetium metal, pieces

HEALTH HAZARDS (ACUTE AND CHRONIC)

To the best of our knowledge the chemical, physical and toxicological properties of Lutetium metal have not been thoroughly investigated and recorded.

Lutetium is considered a rare earth metal. These metals are moderately to highly toxic. The symptoms of toxicity of the rare earth elements include writhing, ataxia, labored respiration, walking on the toes with arched back and sedation. The rare earth elements exhibit low toxicity by ingestion exposure. However, the intraperitoneal route is highly toxic while the subcutaneous route is poison to moderately toxic. The production of skin and lung granulomas after exposure to them requires extensive protection to prevent such exposure. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

INHALATION:

Acute: May cause irritation to the respiratory tract and mucous membrane. Dusts may cause asthma attacks and lung damage such as lung granulomas. Large doses may cause writhing, loss of muscle coordination, labored respiration, sedation, hypotension and cardiovascular collapse. Chronic: Prolonged or repeated inhalation may cause writhing, loss of muscle coordination, labored

Materion Advanced Chemicals Inc.

respiration, sedation, hypotension and cardiovascular collapse.

INGESTION: Acute: May cause gastrointestinal irritation. Chronic: May affect the coagulation rate of the blood.

SKIN: Acute: May cause irritation, rashes and skin granulomas. Chronic: May cause dermatitis, sensitivity to heat, itching and skin lesions.

EYE: Acute: May cause irritation. Chronic: No chronic health effects recorded.

TARGET ORGANS: May affect the respiratory system, blood and skin.

CARCINOGENICITY: NTP? No IARC Monographs? No OSHA Regulated? No **RECOMMENDED EXPOSURE LIMITS**

See "Section II"

LD 50 / LC 50

No toxicity data recorded

SIGNS AND SYMPTOMS OF EXPOSURE

INHALATION: May cause writhing, ataxia, labored respiration, walking on the toes with arched back and sedation.

INGESTION: May cause nausea, vomiting, diarrhea, abdominal burning and cramp-like pain.

SKIN: May cause redness, itching and burning.

EYE: May cause redness, itching, burning and watering.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing respiratory disorders.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove victim to fresh air; keep warm and quiet; give oxygen if breathing is difficult and seek medical attention.

INGESTION: Give 1-2 glasses of milk or water and induce vomiting; seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person.

SKIN: Remove contaminated clothing; brush material off skin; wash affected area with mild soap and water; seek medical attention if irritation persists.

EYE: Flush eyes with lukewarm water, lifting upper and lower eyelids, for at least 15 minutes. Seek medical attention if irritation persists.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE Lutetium metal, pieces

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Wear appropriate respiratory and protective equipment specified in section VIII-control measures. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

WASTE DISPOSAL METHOD

Dispose of in accordance with local, state and federal regulations.

HAZARD LABEL INFORMATION:

Store in cool, dry area Store in tightly sealed container Wash thoroughly after handling

PRECAUTIONS TO BE TAKEN IN HANDLING

None

PRECAUTIONS TO BE TAKEN IN STORING

OTHER PRECAUTIONS

None

SECTION VIII- CONTROL MEASURES Lutetium metal, pieces

PROTECTIVE EQUIPMENT SUMMARY - HAZARD LABEL INFORMATION:

NIOSH approved respirator Impervious gloves Safety glasses Clothes to prevent skin contact **RESPIRATORY EQUIPMENT (SPECIFY TYPE)**

NIOSH - approved dust respirator

Materion Advanced Chemicals Inc.

EYE PROTECTION

Safety glasses

PROTECTIVE GLOVES

Rubber gloves

OTHER PROTECTIVE CLOTHING

Protective gear suitable to prevent contamination

VENTILATION

Local Exhaust: To maintain concentration at low exposure levels Special: None Mechanical (Gen): Recommended Other: None

WORK/HYGIENIC/MAINTENANCE PRACTICES

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.

SECTION IX - ADDITIONAL COMMENTS Lutetium metal, pieces

No data available. <u>GENERATED</u> 03/15/2011, <u>REVISION</u> 01/24/1995, <u>DATE CREATED</u> 03/26/1991