SUPPLIER



MATERIAL SAFETY DATA SHEET

GENERATED 03/15/2011, REVISION 01/15/2002, DATE CREATED 10/31/1991

SECTION I - PRODUCT IDENTIFICATION Yttrium metal, pieces

PRODUCT NAME: Yttrium metal, pieces

PRODUCT CODE: Y-MSDS0013
REFERENCE #: 7440-65-5

MANUFACTURER INFORMATION

COMPANY NAME: Materion Advanced Chemicals Inc.

1316 W. St. Paul Avenue Milwaukee, WI 53233

EMERGENCY CONTACT: CHEMTREC (800)424-9300

ALTERNATE EMERGENCY CONTACT: Materion Advanced Chemicals Inc. (414)289-9800

CHEMICAL FAMILY: Metal

CAS NUMBER: 7440-65-5 **RTECS #:** ZG2980000

FORMULA: Y

MOLECULAR WEIGHT: 88.91 UPC/EAN: 231-174-8

SYNONYMS Yttrium metal

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION Yttrium metal, pieces

Hazardous
Components
(Chemical Name)

CAS # Concentration OSHA PEL ACGIH TLV Limits

Yttrium 7440-65-5 0.0 -100.0 % 1 mg/m3 1 mg/m3 NE

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS Yttrium metal, pieces

PHYSICAL STATES: [] Gas [] Liquid [X] Solid

 MELTING POINT:
 1500.00 C - 1522.00 C

 BOILING POINT:
 2927.20 C - 3338.00 C

SPECIFIC GRAVITY (WATER = 1): 4.47 gm/cc

VAPOR PRESSURE (VS. AIR OR MM HG): 0

VAPOR DENSITY (VS. AIR = 1):

EVAPORATION RATE (VS BUTYL ACETATE=1):

SOLUBILITY IN WATER: decomposes

SOLUBILITY NOTES

PERCENT VOLATILE: N.A.

APPEARANCE AND ODOR

Gray-black pieces, no odor. Darkens on exposure to light.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA Yttrium metal, pieces

FLASH PT: N.A.

EXPLOSIVE LIMITS: LEL: NA UEL: NA

EXTINGUISHING MEDIA

USE: Not applicable. Use suitable extinguishing media for surrounding materials and type of fire.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

UNUSUAL FIRE AND EXPLOSION HAZARDS

None recorded

HAZARDOUS COMBUSTION PRODUCTS

SECTION V - REACTIVITY DATA Yttrium metal, pieces

STABILITY: Unstable [] Stable [X]

CONDITIONS TO AVOID - INSTABILITY

None

INCOMPATIBILITY - MATERIALS TO AVOID

Strong acids and bases, strong oxidizing agents, air and light sensitive, moisture sensitive, reacts violently with halogens

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Oxides of yttrium

HAZARDOUS POLYMERIZATION:

Will occur [] Will not occur [X]

CONDITIONS TO AVOID - HAZARDOUS POLYMERIZATION

None

SECTION VI - HEALTH HAZARD DATA Yttrium metal, pieces

HEALTH HAZARDS (ACUTE AND CHRONIC)

To the best of our knowledge the chemical, physical and toxicological properties of yttrium metal have not been thoroughly investigated and recorded.

Yttrium is considered a rare earth metal. These metals are moderately to highly toxic. The symptoms of toxicity of the rare earth elements include writhing, ataxia, labored respiration, walking on the toes with arched back and sedation. The rare earth elements exhibit low toxicity by ingestion exposure. However, the intraperitoneal route is highly toxic while the subcutaneous route is poison to moderately toxic. The production of skin and lung granulomas after exposure to them requires extensive protection to prevent such exposure. (Sax, Dangerous Properties of Industrial Materials, eighth edition)

INHALATION:

Acute: May cause irritation to the respiratory tract and mucous membrane. Dusts may cause asthma attacks lung damage such as lung granulomas.

Chronic: Prolonged or repeated inhalation may cause writhing, loss of muscle coordination, labored respiration, sedation, hypotension, fibrosis and cardiovascular collapse.

INGESTION:

Acute: May cause gastrointestinal irritation.

Chronic: May affect the coagulation rate of the blood.

SKIN:

Acute: May cause irritation.

Chronic: No chronic health effects recorded.

EYE:

Acute: May cause irritation.

Chronic: No chronic health effects recorded.

TARGET ORGANS: May affect the respiratory system, eyes, skin and blood.

CARCINOGENICITY: NTP? No IARC Monographs? No OSHA Regulated? No

RECOMMENDED EXPOSURE LIMITS

See "Section II"

LD 50 / LC 50

No toxicity data recorded

SIGNS AND SYMPTOMS OF EXPOSURE

INHALATION: May cause writhing, ataxia, labored respiration, walking on the toes with arched back and sedation.

INGESTION: May cause nausea, vomiting, diarrhea, abdominal burning and cramp-like pain.

SKIN: May cause redness and itching.

EYE: May cause redness, itching and watering.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing respiratory disorders.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove victim to fresh air; keep warm and quiet; give oxygen if breathing is difficult and seek medical attention.

INGESTION: Give 1-2 glasses of milk or water and induce vomiting; seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person.

SKIN: Remove contaminated clothing; brush material off skin; wash affected area with mild soap and water; seek medical attention if irritation persists.

EYE: Flush eyes with lukewarm water, lifting upper and lower eyelids, for at least 15 minutes. Seek medical attention if irritation persists.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE Yttrium metal, pieces

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Wear appropriate respiratory and protective equipment specified in section VIII-control measures. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

WASTE DISPOSAL METHOD

Dispose of in accordance with local, state and federal regulations.

HAZARD LABEL INFORMATION:

Store in cool, dry area Store in tightly sealed container Wash thoroughly after handling

PRECAUTIONS TO BE TAKEN IN HANDLING

None

PRECAUTIONS TO BE TAKEN IN STORING

Store away from light

OTHER PRECAUTIONS

None

SECTION VIII- CONTROL MEASURES Yttrium metal, pieces

PROTECTIVE EQUIPMENT SUMMARY - HAZARD LABEL INFORMATION:

NIOSH approved respirator

Impervious gloves

Safety glasses

Clothes to prevent skin contact

RESPIRATORY EQUIPMENT (SPECIFY TYPE)

NIOSH - approved dust respirator

EYE PROTECTION

Safety glasses

PROTECTIVE GLOVES

Rubber gloves

OTHER PROTECTIVE CLOTHING

Protective gear suitable to prevent contamination

VENTILATION

Local exhaust ventilation may be necessary to control any air contaminants to within their PELs or TLVs during the use of this product. Good general ventilation is recommended.

WORK/HYGIENIC/MAINTENANCE PRACTICES

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.

SECTION IX - ADDITIONAL COMMENTS Yttrium metal, pieces

No data available.

GENERATED 03/15/2011, **REVISION** 01/15/2002, **DATE CREATED** 10/31/1991