# MATERIAL SAFETY DATA SHEET COTRONICS 700 SERIES CASTABLE CERAMICS

RTC-60 Castable Alumina Ceramic RTC-70 Castable Alumina Ceramic 740

Liquid Alumina Silica

Liquid Fused Silica 750

Rescor LX

760 Liquid Zirconium Oxide 770 Liquid Silicon Carbide

780 Liquid Alumina

310LF Liquid Ceramic Foam

Manufactures Name: COTRONICS CORPORATION

131 47th Street Brooklyn, NY 11232

Emergency Telephone Number: 718-788-5533

SECTION ONE: PRODUCT IDENTIFICATION

Chemical Name And Synonyms: N/A Mixture

Formula:

N/A

Base (part A): Powder

Chemical Family: Refractory Ceramic Composition. Proprietary Alumina, Zirconia,

Silica, Silicon Carbide.

Activator (Part B): Liquid

Chemical Family: Proprietary Water Based Colloid Composition (Alumina, Silica)

All materials contained within are listed on the TSCA Inventory list.

This product is compliant with the RoHS Directive.

SECTION 2: COMPOSITION INFORMATION

A.

As Manufactured

WT. % TVL/PEL

Base:

Respirable Nuisance Dust

100

5 mg/cu m\*

SECTION 3A: BASE (POWDER) PHYSICAL DATA

Boiling Point (°F):

N/A

Specific Gravity Range (H2O = 1):

0.9 - 3.1

Vapor Pressure (mm Hg.):

N/A

Vapor Density (Air=1):

N/A

Percent Volatile by Volume (%):

N/A

Solubility in Water:

Insoluble

Evaporation Rate (=1):

N/A

Appearance and Odor:

Fine Powdered Matrix with Coarse Aggregate

No Odor.

SECTION 3B: ACTIVATOR (LIQUID) PHYSICAL DATA

Activator Supplied with

RTC-70, 740, 750, 760, 780, 360LF, Rescor LX

Boiling Point (°F):

212

Specific Gravity Range (H2O = 1):

1.25 - 2.1

Vapor Pressure (mm Hg.):

24 @ 77°F

Vapor Density (Air=1):

Water 50-70

Percent Volatile by Weight (%): Solubility in Water:

Soluble

Evaporation Rate (=1):

Appearance and Odor:

Opalescent liquid No Odor.

HIMS RATING Health = 1 Fire = 0 Reactivity = 0

HAZARD RATING:

 $0 = \ln$ 

<sup>\* (1984-85</sup> ACGIH TLV Booklet, Page 50)

# SECTION 4: FIRE AND EXPLOSION HAZARD DATA

**Extinguishing Media:** 

N/A

Flash Point (Method Used):

N/A

Flammable Limit:

N/A

Unusual Fire And Explosive Hazards: LEL = N/A

Special Fire Fighting Procedures:

UEL = N/A

# SECTION 5: HEALTH HAZARD DATA

Primary Route Of Entry: Inhalation.

Effects of Overexposure: Nuisance dust may cause Nasal, Throat or Lung irritation or discomfort May aggravate Bronchial disorders. Slight dermatological irritation after prolonged skin contact.

Emergency And First Aid Procedures: Flush eyes and skin with copious quantities of water. Get immediate medical attention for eyes. If swallowed, consult physician immediately.

# SECTION 6: FIRE, EXPLOSIVE AND REACTIVITY DATA

Stability:

Stable

Incompatibility (Materials to Avoid):

None

Hazardous Decomposition Products:

None

Hazardous Polymerization:

Will Not Occur

#### SECTION 7: SPILL OR LEAK PROCEDURES

# Steps to be Taken in Case Material is Released or Spilled:

Sweep up spilled powder and dispose in approved industrial waste container. Hose spilled neat cement paste with water, immediately. Cement is not water soluble after setting up. Waste Disposal Method: Approved industrial waste disposal means.

### SECTION 8: SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type):

Dust respirator in compliance with OSHA Standard currently 29 CFR 1910.134 (NIOSH approved, air purifying, half mask or full face-piece respirator with appropriate filter pad or cartridge (s)).

Ventilation: Local Exhaust: Follow OSHA Standard 29 CFR 1910.94. Mechanical (General): Follow OSHA Standard 29 CFR 1910.94.

#### SECTION 8: SPECIAL PRECAUTIONS

This product as manufactured contains silicate which could transform upon heating to mullet and crystolbalite (a form of crystalline silica). Removal of this product after use may result in the generation of dust. Repeated inhalation of respirable free crystalline silica is derived from the formula

> 10 mg/cu m 1/2(----)# % Respirable quartz +

Disclaimer: The information supplied is not to be taken as a warranty or representation for which Cotronics Corp. assumes legal responsibility. It is offered solely for your consideration, investigation and verification. all risk of use, singly or in combination with other products, whether or not in accordance with the instructions, directions, or suggestions is borne by the user.

DATE REVISED: 01/07/09 DATE PREPARED: 11/01/85

significant 1 = Non-Toxic, Slight 2 = Moderate 3 = High 4 = Extreme

<sup>\*(</sup>Reference 1984-85 ACGIH TLV Booklet, Page 34). Appropriate ventilation should be provided and protective equipment should be worn in compliance with OSHA standard currently 29 CFR 1910.134 (NIOSH approved, air purifying, half mask or full face-piece respirator with appropriate filter pad or cartridge(s)).