

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Date of issue: 05/19/2014 Version 1.0

#### **SECTION 1.Identification**

### **Product identifier**

Product number AX0120

Product name Acetone GR ACS

CAS-No. 67-64-1

## Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

# Details of the supplier of the safety data sheet

Company EMD Millipore Corporation | 290 Concord Road, Billerica, MA 01821,

United States of America | General Inquiries: +1-978-715-4321 | Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5)

Emergency telephone 800-424-9300 CHEMTREC (USA)

+1-703-527-3887 CHEMTREC (International)

24 Hours/day; 7 Days/week

### **SECTION 2. Hazards identification**

## **GHS Classification**

Flammable liquid, Category 2, H225

Eye irritation, Category 2, H319

Specific target organ systemic toxicity - single exposure, Category 3, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

## **GHS-Labeling**

Hazard pictograms





Signal Word
Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number AX0120 Version 1.0

Product name Acetone GR ACS

### Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### **OSHA Hazards**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This information is based on 29 CFR 1910.1200 criteria prior to adoption of the GHS and may deviate from the GHS information.

#### Other hazards

None known.

# SECTION 3. Composition/information on ingredients

Formula CH₃COCH₃ C₃H₅O (Hill)

Molar mass 58.08 g/mol

## Hazardous ingredients

Chemical Name (Concentration)

CAS-No.

acetone (>= 90 % - <= 100 % )

67-64-1

Exact percentages are being withheld as a trade secret.

### **SECTION 4. First aid measures**

#### Description of first-aid measures

Inhalation

After inhalation: fresh air. Call in physician.

Skin contact

After skin contact: wash off with plenty of water. Remove contaminated clothing.

Eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist.

Ingestion

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

Never give anything by mouth to an unconscious person.

# Most important symptoms and effects, both acute and delayed

irritant effects, Drowsiness, Dizziness, narcosis, Nausea, Vomiting, Stomach/intestinal disorders,

Headache, drowziness, Salivation, Coma

Risk of corneal clouding.

Drying-out effect resulting in rough and chapped skin.

# Indication of any immediate medical attention and special treatment needed

No information available.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number AX0120 Version 1.0

Product name Acetone GR ACS

## **SECTION 5. Fire-fighting measures**

## Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

# Special hazards arising from the substance or mixture

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at ambient temperatures.

Pay attention to flashback.

Development of hazardous combustion gases or vapors possible in the event of fire.

# Advice for firefighters

Special protective equipment for fire-fighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by

keeping a safe distance or by wearing suitable protective clothing.

Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

Remove container from danger zone and cool with water.

#### SECTION 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid substance contact. Do not breathe vapors, aerosols.

Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders: Protective equipment see section 8.

#### **Environmental precautions**

Do not empty into drains. Risk of explosion.

#### Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills.

Observe possible material restrictions (see sections 7 and 10).

Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

## SECTION 7. Handling and storage

## Precautions for safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapors/aerosols.

Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number AX0120 Version 1.0

Product name Acetone GR ACS

# Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Protected from light.

Store at room temperature.

## SECTION 8. Exposure controls/personal protection

### Exposure limit(s)

Ingredients

Basis	Value	Threshold limits	Remarks	
acetone 67-64-1				
ACGIH	Time Weighted Average (TWA):	500 ppm		
	Short Term Exposure Limit (STEL):	750 ppm		
NIOSH/GUIDE	Recommended	250 ppm		
	exposure limit (REL):	590 mg/m³		
OSHA_TRANS	PEL:	1,000 ppm		
		2,400 mg/m <sup>3</sup>		
Z1A	Time Weighted Average	750 ppm		
	(TWA):	1,800 mg/m³		

Short Term Exposure

Limit (STEL):

#### **Engineering measures**

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

#### Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

### Hygiene measures

Immediately change contaminated clothing. Apply skin- protective barrier cream. Wash hands and face after working with substance.

1,000 ppm 2,400 mg/m<sup>3</sup>

## Eye/face protection

Safety glasses

## Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

### Other protective equipment:

Flame retardant antistatic protective clothing

### Respiratory protection

required when vapors/aerosols are generated.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

AX0120 Product number Version 1.0

Product name Acetone GR ACS

## SECTION 9. Physical and chemical properties

Physical state liquid

Color colorless

Odor fruity

Odor Threshold 0.1 - 662.5 ppm

pН 5 - 6

> at 395 g/l 68 °F (20 °C)

Melting point -95.4 °C

Boiling point/boiling range 133.2 °F (56.2 °C)

at 1,013 hPa

< -4 °F (< -20 °C) Flash point

Method: DIN 51755 Part 1

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit 2.6 %(V)

Upper explosion limit 12.8 %(V)

Vapor pressure 233 hPa

at 68 °F (20 °C)

Relative vapor density 2.01

0.79 g/cm<sup>3</sup> Density

at 68 °F (20 °C)

Relative density No information available.

Water solubility at 68 °F (20 °C)

soluble

Partition coefficient: n-

log Pow: -0.24 octanol/water (experimental)

Bioaccumulation is not expected. (Lit.)

No information available. Autoignition temperature

Decomposition temperature Distillable in an undecomposed state at normal pressure.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number Product name	AX0120 Acetone GR ACS	Version 1.0
Viscosity, dynamic	0.32 mPa.s at 68 °F (20 °C)	
Explosive properties	Not classified as explosive.	
Oxidizing properties	none	
Ignition temperature	869 °F (465 °C) DIN 51794	
Conductivity	0.01 μS/cm at 68 °F (20 °C)	

## SECTION 10. Stability and reactivity

## Reactivity

Vapors may form explosive mixture with air.

## **Chemical stability**

Sensitivity to light Sensitive to air.

# Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapors with:

chromosulfuric acid, chromyl chloride, ethanolamine, Fluorine, Strong oxidizing agents, strong reducing agents, Nitric acid, chromium(VI) oxide

Risk of explosion with:

nonmetallic oxyhalides, halogen-halogen compounds, Chloroform, nitrating acid, nitrosyl compounds, hydrogen peroxide, halogen oxides, organic nitro compounds, peroxi compounds

Exothermic reaction with:

Bromine, Alkali metals, alkali hydroxides, Halogenated hydrocarbon, Sulfur dichloride, phosphorous oxichloride

## Conditions to avoid

Warming.

# Incompatible materials

rubber, various plastics

# Hazardous decomposition products

no information available

# **SECTION 11. Toxicological information**

## Information on toxicological effects

Likely route of exposure Inhalation, Eye contact, Skin contact

Target Organs

Eyes

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number AX0120 Version 1.0

Product name Acetone GR ACS

Skin

Respiratory system Central nervous system

Acute oral toxicity

LD50 rat: 5,800 mg/kg (RTECS)

Symptoms: Stomach/intestinal disorders, Risk of aspiration upon vomiting., Pulmonary failure possible after aspiration of vomit.

Acute inhalation toxicity LC50 rat: 76 mg/l; 4 h (Lit.)

Symptoms: mucosal irritations

absorption

Acute dermal toxicity LD50 rabbit: 20,000 mg/kg

(IUCLID)

Skin irritation

rabbit

Result: No irritation (External MSDS)

Repeated exposure may cause skin dryness or cracking.

Possible damages: slight irritation

Eye irritation

rabbit

Result: Eye irritation (External MSDS)

Causes serious eye irritation.

Risk of corneal clouding.

Sensitization

Sensitization test: guinea pig

Result: negative

(Lit.)

Genotoxicity in vivo

Mutagenicity (mammal cell test): micronucleus.

Result: negative

(National Toxicology Program)

Genotoxicity in vitro

Mutagenicity (mammal cell test): chromosome aberration.

Result: negative

(National Toxicology Program)

Ames test

Result: negative

(National Toxicology Program)

Carcinogenicity

Did not show carcinogenic effects in animal experiments. (IUCLID)

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number AX0120 Version 1.0

Product name Acetone GR ACS

Specific target organ systemic toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ systemic toxicity - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Regarding the available data the classification criteria are not fulfilled.

Carcinogenicity

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

## **Further information**

After absorption:

Headache, Salivation, Nausea, Vomiting, Dizziness, narcosis, Coma Handle in accordance with good industrial hygiene and safety practice.

## **SECTION 12. Ecological information**

### **Ecotoxicity**

Toxicity to fish

LC50 Oncorhynchus mykiss (rainbow trout): 5,540 mg/l; 96 h (Lit.)

Toxicity to daphnia and other aquatic invertebrates

EC50 Daphnia magna (Water flea): 6,100 mg/l; 48 h (Lit.)

EC5 E.sulcatum: 28 mg/l; 72 h (maximum permissible toxic concentration) (Lit.)

Toxicity to algae

IC5 M.aeruginosa: 530 mg/l; 8 d (maximum permissible toxic concentration) (IUCLID)

Toxicity to bacteria

EC50 activated sludge: 59 - 67.4 mg/l; 30 min (Lit.)

EC5 Pseudomonas putida: 1,700 mg/l; 16 h (maximum permissible toxic concentration) (IUCLID)

#### Persistence and degradability

Biodegradability 91 %; 28 d

(IUCLID)

Readily biodegradable.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number AX0120 Version 1.0

Product name Acetone GR ACS

Biochemical Oxygen Demand (BOD)

1,850 mg/g (5 d)

(IUCLID)

Chemical Oxygen Demand (COD)

2,070 mg/g

(IUCLID)

Theoretical oxygen demand (ThOD)

2,200 mg/g

(Lit.)

## Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: -0.24 (experimental)

Bioaccumulation is not expected. (Lit.)

## Mobility in soil

No information available.

Additional ecological information

Discharge into the environment must be avoided.

## **SECTION 13. Disposal considerations**

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

### **SECTION 14. Transport information**

Land transport (DOT)

UN 1090
Proper shipping name UN 1090
ACETONE

Class 3
Packing group II
Environmentally hazardous ---

Air transport (IATA)

**UN 1090 Proper shipping name**UN 1090
ACETONE

Class 3
Packing group II
Environmentally hazardous -Special precautions for user no

Sea transport (IMDG)

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number AX0120 Version 1.0

Product name Acetone GR ACS

**UN 1090 Proper shipping name**UN 1090
ACETONE

Class 3
Packing group II
Environmentally hazardous --Special precautions for user
EmS yes
F-E S-D

## **SECTION 15. Regulatory information**

## **United States of America**

### **OSHA Hazards**

Flammable Liquid

Eye irritant

Skin irritant

Respiratory irritant

Harmful if inhaled.

Harmful if swallowed.

Target organ effects

This information is based on 29 CFR 1910.1200 criteria prior to adoption of the GHS, and may deviate from the GHS information on the label and in section 2.

#### SARA 311/312 Hazards

Fire Hazard

Acute Health Hazard

Chronic Health Hazard

### **SARA 313**

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **SARA 302**

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311,

Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311,

Table 117.3.

#### **DEA List I**

Not listed

### **DEA List II**

Listed

Ingredients

acetone 67-64-1

### **US State Regulations**

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number AX0120 Version 1.0

Product name Acetone GR ACS

### Massachusetts Right To Know

Ingredients acetone

## Pennsylvania Right To Know

Ingredients acetone

## New Jersey Right To Know

Ingredients acetone

## California Prop 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

### Notification status

TSCA: All components of the product are listed in the TSCA-inventory.

DSL: All components of this product are on the Canadian DSL.

## **SECTION 16. Other information**

### Training advice

Provide adequate information, instruction and training for operators.

## Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

## Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Date of issue: 05/19/2014

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.