

according to Regulation (EC) No. 1907/2006

Revision Date 19.09.2016

Version 3.3

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

REACH Registration Number A registration number is not available for this substance as the

substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a

later registration deadline.

CAS-No. 8042-47-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Pharmaceutical production, Reagent for development and research,

Cosmetic raw material

For additional information on uses please refer to the Merck Chemicals

portal (www.merckgroup.com).

1.3 Details of the supplier of the safety data sheet

Company Merck KGaA * 64271 Darmstadt * Germany * Phone:+49 6151 72-0

Responsible Department LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone

+44 870 1906777

number

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1, H304

For the full text of the H-Statements mentioned in this Section, see Section 16.

according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur,BP,NF,JP

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Danger

Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

CAS-No. 8042-47-5

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

3.1 Substance

EC-No. 232-455-8

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical Name (Concentration)

CAS-No. Registration number Classification

white mineral oil (petroleum) (<= 100 %)

8042-47-5 *)

Aspiration hazard, Category 1, H304

^{*)} A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

For the full text of the H-Statements mentioned in this Section, see Section 16.

3.2 Mixture

Not applicable

SECTION 4. First aid measures

4.1 Description of first aid measures

After inhalation: fresh air.

After skin contact: wash off with plenty of water. Remove contaminated clothing.

After eye contact: rinse out with plenty of water.

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Call a physician immediately. Pulmonary failure possible after aspiration of vomit.

4.2 Most important symptoms and effects, both acute and delayed

Stomach/intestinal disorders, Pneumonia

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Combustible.

Vapours are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Special protective equipment for firefighters

In the event of fire, wear self-contained breathing apparatus.

according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders: Protective equipment see section 8.

6.2 Environmental precautions

Do not empty into drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills.

Observe possible material restrictions (see sections 7 and 10).

Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed.

Recommended storage temperature see product label.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components

Basis Value Threshold Remarks

limits

white mineral oil (petroleum) (8042-47-5)

ELV (IE) Time Weighted Average 5 mg/m³ Form of exposure: Mist.

(TWA):

Short Term Exposure 10 mg/m³ Form of exposure: Mist.

Limit (STEL):

Time Weighted Average 5 mg/m³ Form of exposure: Inhalable fraction.

(TWA):

Time Weighted Average 0.2 mg/m³ Form of exposure: Inhalable fraction.

(TWA):

Recommended monitoring procedures

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms DIN EN 482 and DIN EN 689.

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection

Safety glasses

Hand protection

full contact:

Glove material: Nitrile rubber

according to Regulation (EC) No. 1907/2006

Catalogue No.

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

107174

Glove thickness: 0.11 mm

Break through time: > 480 min

splash contact:

Glove material: Nitrile rubber
Glove thickness: 0.11 mm
Break through time: > 480 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 741 Dermatril® L (full contact), KCL 741 Dermatril® L (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment protective clothing

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective
devices are carried out according to the instructions of the producer. These measures have to be
properly documented.

Environmental exposure controls

Do not empty into drains.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form liquid

Colour colourless

Odour mild

according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

Odour Threshold No information available.

pH No information available.

pour point ca. -15 °C

Boiling point/boiling range 300 - 450 °C

at 1,013 hPa

Flash point > 180 °C

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit No information available.

Upper explosion limit No information available.

Vapour pressure 0.0001 hPa

at 20 °C

Relative vapour density No information available.

Density 0.85 g/cm³

at 20 °C

Relative density No information available.

Water solubility at 20 °C

practically insoluble

Partition coefficient: n-

octanol/water Not applicable

Auto-ignition temperature 325 - 355 °C

Decomposition temperature > 350 °C

according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur,BP,NF,JP

Viscosity, dynamic 30 - 40 mPa.s

at 20 °C

Explosive properties Not classified as explosive.

Oxidizing properties none

9.2 Other data

Ignition temperature > 300 °C

Viscosity, kinematic ca.16 mm2/s

at 40 °C

SECTION 10. Stability and reactivity

10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with:

Strong oxidizing agents

Risk of explosion with:

nitrates, chlorates, perchlorates

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

no information available

10.6 Hazardous decomposition products

no information available

according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur,BP,NF,JP

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

LD50 Rat: > 5,000 mg/kg

(External MSDS)

Symptoms: Stomach/intestinal disorders

Acute inhalation toxicity

LC50 Rat: > 5 mg/l; 4 h; dust/mist

(External MSDS)

Symptoms: Inhalation may lead to the formation of oedemas in the respiratory tract., Possible

damages:, Pneumonia

Acute dermal toxicity

LD50 Rabbit: > 2,000 mg/kg

(External MSDS)

Skin irritation

Rabbit

Result: No skin irritation

(External MSDS)

Eye irritation

Rabbit

Result: No eye irritation

(External MSDS)

Sensitisation

Sensitisation test (Magnusson and Kligman): Guinea pig

Result: negative

Method: OECD Test Guideline 406

Germ cell mutagenicity

according to Regulation (EC) No. 1907/2006

Catalogue No.

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

107174

Genotoxicity in vitro

Ames test

Result: negative

(External MSDS)

Mutagenicity (mammal cell test): chromosome aberration.

Result: negative

(External MSDS)

Carcinogenicity

Did not show carcinogenic effects in animal experiments. (External MSDS)

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

This information is not available.

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

11.2 Further information

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

12.1 Toxicity

Toxicity to fish

LC50 Leuciscus idus (Golden orfe): > 1,000 mg/l; 96 h

OECD Test Guideline 203

according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur,BP,NF,JP

Toxicity to daphnia and other aquatic invertebrates

Daphnia magna (Water flea): > 100 mg/l; 48 h

OECD Test Guideline 202

Toxicity to algae

Pseudokirchneriella subcapitata (green algae): >= 100 mg/l; 72 h

OECD Test Guideline 201

12.2 Persistence and degradability

Biodegradability

31.3 %; 28 d

OECD Test Guideline 301F

Inherently biodegradable.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water

Not applicable

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

12.6 Other adverse effects

Discharge into the environment must be avoided.

according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

SECTION 13. Disposal considerations

Waste treatment methods

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

Notice Directive on waste 2008/98/EC.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 - 14.6 Not classified as dangerous in the meaning of transport

regulations.

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

14.1 - 14.6 Not classified as dangerous in the meaning of transport

regulations.

Sea transport (IMDG)

14.1 - 14.6 Not classified as dangerous in the meaning of transport

regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard SEVESO III
Legislation Not applicable

according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

Occupational restrictions Take note of Dir 94/33/EC on the protection of young people at

work.

Regulation (EC) No 1005/2009 on substances that not regulated

deplete the ozone layer

Regulation (EC) No 850/2004 of the European not regulated

Parliament and of the Council of 29 April 2004 on

persistent organic pollutants and amending

Directive 79/117/EEC

Substances of very high concern (SVHC)

This product does not contain substances

of very high concern according to

Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory

concentration limit of $\geq 0.1 \%$ (w/w).

National legislation

Storage class 10 - 13

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H304 May be fatal if swallowed and enters airways.

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms



according to Regulation (EC) No. 1907/2006

Catalogue No. 107174

Product name Paraffin highly liquid Ph Eur, BP, NF, JP

Signal word

Danger

Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Regional representation

Merck Chemicals Ltd * Boulevard Industrial Park * Padge Road * Beeston * Nottingham * NG9 2JR * United Kingdom * Tel.: +44 1159 430840 * Fax: +44 1159 430 951 * information@merckchem.co.uk.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.