

ACE HARDWARE CORP -- 197A125, SEVEN STAR QUICK DRY RUST (SUPDAT) -- 8010-00N028995

=====
Product Identification
=====

Product ID:197A125, SEVEN STAR QUICK DRY RUST (SUPDAT)

MSDS Date:07/01/1994

FSC:8010

NIIN:00N028995

MSDS Number: CCYDM

=== Responsible Party ===

Company Name:ACE HARDWARE CORP

Address:21901 S CENTRAL AVE

City:MATTESON

State:IL

ZIP:60443

Country:US

Info Phone Num:708-720-0600

Emergency Phone Num:708-990-6600

CAGE:ACEHA

=== Contractor Identification ===

Company Name:ACE HARDWARE CORPORATION

Address:21901 SOUTH CENTRAL AVENUE

City:MATTESON

State:IL

ZIP:60443

Country:US

Phone:708-720-0600

CAGE:ACEHA

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM; (ALUMINUM FLAKED METAL) (SARA 313)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 0.1%

OSHA PEL:15 MG/M3 DUST

ACGIH TLV:10 MG/M3 DUST

Ingred Name:SODIUM ALUMINOSILICATE; (AMORPHOUS SILICATE)

CAS:1344-00-9

Fraction by Wt: 0.2%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:XYLENE; (NAPHTHA) (SARA 313) (CERCLA)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 34.4%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 150 STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC; (AROMATIC HYDROCARBON SOLVENT)
CAS:64742-95-6
RTECS #:WF3400000
Fraction by Wt: 26.4%
OSHA PEL:100 PPM (MFR)
ACGIH TLV:100 PPM (MFR)

Ingred Name:COPPER; (COPPER FLAKED METAL) (SARA 313) (CERCLA)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 17.9%
OSHA PEL:0.1MG/M3 FUME;1 DUST
ACGIH TLV:0.2 MG/M3 FUME
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC; (ZINC FLAKED METAL) (SARA 313) (CERCLA)
CAS:7440-66-6
RTECS #:ZG8600000
Fraction by Wt: 5.8%
OSHA PEL:N/K
ACGIH TLV:N/K
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYES, SKIN AND

RESPIRATORY SYSTEM MAY OCCUR ON OVEREXPOSURE. MAY ALSO CAUSE NERVOUS SYSTEM DEPRESSION. CHRONIC: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA AND LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS.

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

=====
First Aid Measures
=====

First Aid:INGEST: CALL MD IMMEDIATELY . INHAL: IF INHALED - REMOVE FROM EXPOSURE - RESTORE BREATHING - KEEP WARM AND QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point:45.0F,7.2C

Lower Limits:0.7%

Extinguishing Media:FOR DRY SOLIDS, USE WATER, FOAM, CARBON DIOXIDE, DRY CHEMICALS.

Fire Fighting Procedures:USE NIOSH APPRVD SCBA & FULL PROT EQUIP . WATER MAY BE USED TO COOL CLSD CNTNRS TO PVNT PRESS BUILDUP & POSS AUTOIGNIT/EXPLO WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIP, SPARKS & OPEN FLAME. HEAT MAY CAUSE PRESS BUILDUP IN CLOSED CNTNRS. WATER MAY BE USED TO COOL.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:CONTENTS ARE COMBUST. KEEP AWAY FROM HEAT & OPEN FLAME. USE APPRVD BONDING & GROUNDING PROCS. TRANSFER ONLY TO APPRVD, PROPERLY MARKED CONTAINERS.

Other Precautions:KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY

DELIBERATELY INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:PROPERLY FITTED ORGANIC VAPOR/PARTICULATE
RESPIRATOR APPROVED BY NIOSH.
Ventilation:LOCAL EXHAUST: PREFERABLE.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .
Other Protective Equipment:ANSI APPROVED EYE WASH & DELUGE SHOWER .
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
MFR'S TRADE NAME/PART NO: PREVENTATIVE OIL ENAMEL - GOLD.

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:280F,138C
Vapor Density:HVR/AIR
Spec Gravity:1.16 (H*20=1)
Evaporation Rate & Reference:SLOWER/ETHER (BU AC=1)
Appearance and Odor:GOLD FLAKE PIGMENTED LIQUID WITH SOLVENT ODOR.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:BY FIRE - CARBON DIOXIDE, CARBON
MONOXIDE.

=====
Disposal Considerations
=====

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their

particular situation.